## JCB WHEELED LOADERS 436E STAGE IIIA/T3 (1410000->) (2008-2013)



<b>ENGINE</b> Cummins QSB6.7 Capacity: 14 liter		
USE		CLIMATE
Normal		Moderate
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	PRODUCT RECOMMENDATION 3
Agridiesel MSP 15W-40	Agridiesel CRD+ 15W-40	Dieselfleet CD+ 15W-40

Check every 10 hours, change every 500 hours/ 6 months

<b>DIFFERENTIAL FRONT</b> Graziano PR12 Capacity: 39 liter (+ hub reductions)		
USE		CLIMATE
Normal		Moderate
PRODUCT RECOMMENDATION 1		
Gearlube LS 80W-90		
Check every 6 months/ 500 hours, change	every 12 months/ 1000 hours	
USE		CLIMATE
Initial service		Moderate
PRODUCT RECOMMENDATION 1		
Gearlube LS 80W-90		
Change every 100 hours		

<b>DIFFERENTIAL FRONT</b> MT-I Capacity: 35 liter			
USE		CLIMATE	
Normal		Moderate	
PRODUCT RECOMMENDATION 1			
Agrifluid HT			
Check every 6 months/ 500 hours,	change every 12 months/ 1000 hours		
USE		CLIMATE	
Initial convice		Modorato	

USE	CLIMATE
Initial service	Moderate
PRODUCT RECOMMENDATION 1	
Agrifluid HT	
Change every 100 hours	·

## JCB WHEELED LOADERS 436E STAGE IIIA/T3 (1410000->) (2008-2013)



<b>DIFFERENTIAL REAR</b> Graziano PR12 Capacity: 39 liter (+ hub reductions)		
USE		CLIMATE
Normal		Moderate
PRODUCT RECOMMENDATION 1		
Gearlube LS 80W-90		
Check every 6 months/ 500 hours, change	every 12 months/ 1000 hours	
USE		CLIMATE
Initial service		Moderate
PRODUCT RECOMMENDATION 1		
Gearlube LS 80W-90		
Change every 100 hours		

<b>DIFFERENTIAL REAR</b> MT-I Capacity: 23 liter		
USE		CLIMATE
Normal		Moderate
PRODUCT RECOMMENDATION 1		
Agrifluid HT		
Check every 6 months/ 500 hours, change	every 12 months/ 1000 hours	

USE CLIMATE
Initial service Moderate
PRODUCT RECOMMENDATION 1

Agrifluid HT

Change every 100 hours

TRANSMISSION ZF 4WG190 4/3 Capacity: 32,5 liter	
USE	CLIMATE
Normal	Mediterranean
PRODUCT RECOMMENDATION 1	
Multifleet SCD 20W-20	

Check every 50 hours, change every 1000 hours/ 12 months

USE		CLIMATE
Normal		Moderate
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	PRODUCT RECOMMENDATION 3
Agrifluid Synth XHP Ultra	Agrifluid HT-Plus	Agrifluid HT
Chook over 50 hours shance over	1000 hours/12 months	<u>'</u>

Check every 50 hours, change every 1000 hours/ 12 months

## JCB WHEELED LOADERS 436E STAGE IIIA/T3 (1410000->) (2008-2013)



HYDRAULIC SYSTEM Capacity: 210 liter		
USE		CLIMATE
Flexible (max)		Moderate
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	
Perlus Biosynth 46	Perlus H 46	
Check every 10 hours, change every 2000	) hours/ 24 months	
USE		CLIMATE
Flexible, fluid analysis		Moderate
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	
Perlus Biosynth 46	Perlus H 46	
Check every 6 months/ 500 hours		

GREASE POINTS/NIPPLES	
USE	CLIMATE
Normal	Moderate
PRODUCT RECOMMENDATION 1	
HT Q9 High Grade Grease	

COOLING SYSTEM Capacity: 35 liter		
USE		CLIMATE
Flexible (max)		Moderate
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	PRODUCT RECOMMENDATION 3
Coolant SP 15+	Coolant SP 12	Coolant -38 Organic NF

Check every 6 months/ 500 hours, change every 24 months/ 2000 hours

The data mentioned in this product information sheet is meant to enable the reader to orientate himself about the properties and possible applications of our products. Although this overview is composed with all possible care on the stated date, the compiler does not accept any liability for damages caused by incompleteness and/or inaccuracies in this information, especially when these are caused by obvious typing errors. The terms of delivery of the supplier apply to all product supplies. The reader is advised, especially for critical applications, to make the final product choice in consultation with the supplier. Due to continual product research and development, the information contained herein is subject to changes without notification.