JCB TELESCOPIC HANDLERS (USA) LOADALL/AGRI 527-58 USA (81 KW) STAGE IIIB/T4I (2014 AND AFTER)



ENGINE JCB Ecomax T4i Capacity: 15 liter	
USE	CLIMATE
Normal	Moderate
PRODUCT RECOMMENDATION 1	
Armado Synth MSP 5W-40	

Check every 10 hours, change every 500 hours/ 6 months

DIFFERENTIAL FRONT Capacity: 17,7 liter		
USE		CLIMATE
Normal		Moderate
PRODUCT RECOMMENDATION 1		
Agrifluid HT		
Check every 50 hours, change every 6 mo	nths/ 500 hours	

DIFFERENTIAL REAR Capacity: 10 liter	
USE	CLIMATE
Normal	Moderate
PRODUCT RECOMMENDATION 1	
Agrifluid HT	

Check every 50 hours, change every 6 months/ 500 hours

HUB REDUCTIONS FRONT Capacity: 1,9 liter (each hub)	
USE	CLIMATE
Normal	Moderate
PRODUCT RECOMMENDATION 1	
Agrifluid HT	

Check every 1 months/ 100 hours, change every 12 months/ 1000 hours

HUB REDUCTIONS REAR Capacity: 2 liter (each hub)		
USE		CLIMATE
Normal		Moderate
PRODUCT RECOMMENDATION 1		
Agrifluid HT		
Charle avery 1 manths/ 100 hours abanas	vary 12 manths/ 1000 hours	:

Check every 1 months/ 100 hours, change every 12 months/ 1000 hours

JCB TELESCOPIC HANDLERS (USA) LOADALL/AGRI 527-58 USA (81 KW) STAGE IIIB/T4I (2014 AND AFTER)



TRANSMISSION Synchro Shuttle SS700/750 Capacity: 11,5 liter (Change capacity), Capacity: 13,5 liter (Dry fill)		
USE		CLIMATE
Normal		Mediterranean
PRODUCT RECOMMENDATION 1		
Gear Oil Alcat 30		
Check every 10 hours, change every 1000 hours/ 12 months		
USE		CLIMATE

Normal		Moderate
PRODUCT RECOMMENDATION 1		
Gear Oil Alcat 10W		
Check evenu 10 hours change evenu 1000 hours/ 12 months		

Check every 10 hours, change every 1000 hours/ 12 months

TRANSMISSION POWERSHIFT PS760 Capacity: 21 liter (Change capacity), Capacity: 23 liter (Dry fill)			
USE		CLIMATE	
Normal		Mediterranean	
PRODUCT RECOMMENDATION 1			
Gear Oil Alcat 30			

Check every 10 hours, change every 1000 hours/ 12 months

USE		CLIMATE
Normal		Moderate
PRODUCT RECOMMENDATION 1		
Gear Oil Alcat 10W		
Check even 10 hours change even 1000	hours/12 months	

Check every 10 hours, change every 1000 hours/ 12 months

HYDRAULIC SYSTEM Capacity: 116 liter (Hydraulic tank)		
USE		CLIMATE
Normal		Tropical
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	
Perlus H 46	Perlus AF 46	

Check every 50 hours, change every 2000 hours/ 24 months

use Normal		climate Moderate
PRODUCT RECOMMENDATION 1 Perlus H 32	PRODUCT RECOMMENDATION 2 Perlus AF 32	
Check every 50 hours, change every 2000 hours/ 24 months		

JCB TELESCOPIC HANDLERS (USA) LOADALL/AGRI 527-58 USA (81 KW) STAGE IIIB/T4I (2014 AND AFTER)



HYDRAULIC BRAKE SYSTEM			
USE		CLIMATE	
Normal		Moderate	
PRODUCT RECOMMENDATION 1			
Perlus H 15			

Check every 10 hours, change every 2000 hours/24 months

GREASE POINTS/NIPPLES			
USE		CLIMATE	
Preferred		Moderate	
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2		
HT Q9 High Grade Grease	Labora Grease		

COOLING SYSTEM Capacity: 28 liter			
USE		CLIMATE	
Normal		Moderate	
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	PRODUCT RECOMMENDATION 3	
Coolant SP 15+	Coolant SP 12	Coolant -38 Organic NF	
Check every 10 hours, change every 2000 hours/24 months			

The data mentioned in this product information sheet is meant to enable the reader to orientate himself about the properties and possible applications of our products. Although this overview is composed with all possible care on the stated date, the compiler does not accept any liability for damages caused by incompleteness and/or inaccuracies in this information, especially when these are caused by obvious typing errors. The terms of delivery of the supplier apply to all product supplies. The reader is advised, especially for critical applications, to make the final product choice in consultation with the supplier. Due to continual product research and development, the information contained herein is subject to changes without notification.