## JCB TELESCOPIC HANDLERS 520-50 PERKINS 1004-4 (1996-2004)



ENGINE Perkins 1004-4		
USE		CLIMATE
Normal		Mediterranean
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	
Dieselfleet CD+ 15W-40	Multifleet SHPD 15W-40	
USE		CLIMATE
Normal		Moderate
PRODUCT RECOMMENDATION 1		
Multifleet SHPD 10W-40		
USE		CLIMATE
Normal		Arctic
PRODUCT RECOMMENDATION 1		
Multifleet SCD 10W		

DIFFERENTIAL HUB REDUCTIONS WET BRAKES		
USE		CLIMATE
Normal		Mediterranean
PRODUCT RECOMMENDATION 1		
Agrifluid HT		

DRIVE / STEER AXLE		
USE		CLIMATE
Normal		Mediterranean
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	
Gearlube GL-5 80W-90	Unigear HS GL-3/GL-5 80W-90	

TRANSMISSION Brockhouse DR.4	4	
USE		CLIMATE
Normal		Mediterranean
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	
Gear Oil Alcat 10W	ATF Dexron II-D	

## JCB TELESCOPIC HANDLERS 520-50 PERKINS 1004-4 (1996-2004)



TRANSMISSION JCB			
USE		CLIMATE	
Normal		Mediterranean	
PRODUCT RECOMMENDATION 1			
ATF-F (Ford)			

TRANSMISSION Powershift/ShuttleReverser/Warner			
USE		CLIMATE	
Normal		Mediterranean	
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2		
Gear Oil Alcat 10W	ATF Dexron II-D		

TRANSMISSION SYNCHROMESH Turner		
USE	CLIMATE	
Normal	Mediterranean	
PRODUCT RECOMMENDATION 1		
Multifleet SCD 20W-20		
	-	

HYDRAULIC SYSTEM Capacity: 70 liter (Hydraulic tank)		
use Normal	сымате Mediterranean	
PRODUCT RECOMMENDATION 1 Perlus H 32		

HYDRAULIC BRAKE SYSTEM		
USE		CLIMATE
Normal		Mediterranean
PRODUCT RECOMMENDATION 1		
Perlus H 15		

CLIMATE
Mediterranean

## JCB TELESCOPIC HANDLERS 520-50 PERKINS 1004-4 (1996-2004)



## **GREASE POINTS/NIPPLES TELESCOPIC SLIDING SURFACES**

We are unable to give a standard recommendation for this component. Please contact our service department.

COOLING SYSTEM Capacity: 20 liter		
USE		CLIMATE
Normal		Moderate
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	PRODUCT RECOMMENDATION 3
Coolant SP 15+	Coolant SP 12	Coolant -38 Organic NF

The data mentioned in this product information sheet is meant to enable the reader to orientate himself about the properties and possible applications of our products. Although this overview is composed with all possible care on the stated date, the compiler does not accept any liability for damages caused by incompleteness and/or inaccuracies in this information, especially when these are caused by obvious typing errors. The terms of delivery of the supplier apply to all product supplies. The reader is advised, especially for critical applications, to make the final product choice in consultation with the supplier. Due to continual product research and development, the information contained herein is subject to changes without notification.