

# JCB TELESCOPIC HANDLERS 525-58 (1989-1994)



## ENGINE

USE	CLIMATE
Normal	Mediterranean

PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	
<b>Dieselfleet CD+ 15W-40</b>	<b>Multifleet SHPD 15W-40</b>	

*Change every 250 hours/ 1 months*

USE	CLIMATE
Normal	Moderate

PRODUCT RECOMMENDATION 1		
<b>Multifleet SHPD 10W-40</b>		

*Change every 250 hours/ 1 months*

USE	CLIMATE
Normal	Arctic

PRODUCT RECOMMENDATION 1		
<b>Multifleet SCD 10W</b>		

*Change every 250 hours/ 1 months*

USE	CLIMATE
Initial service	Mediterranean

PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	
<b>Dieselfleet CD+ 15W-40</b>	<b>Multifleet SHPD 15W-40</b>	

*Change every 100 hours*

USE	CLIMATE
Initial service	Moderate

PRODUCT RECOMMENDATION 1		
<b>Multifleet SHPD 10W-40</b>		

*Change every 100 hours*

USE	CLIMATE
Initial service	Arctic

PRODUCT RECOMMENDATION 1		
<b>Multifleet SCD 10W</b>		

*Change every 100 hours*

## DIFFERENTIAL HUB REDUCTIONS WET BRAKES

USE	CLIMATE
Normal	Mediterranean

PRODUCT RECOMMENDATION 1		
<b>Agrifluid HT</b>		

*Change every 1000 hours/ 12 months*

# JCB TELESCOPIC HANDLERS 525-58 (1989-1994)



## DRIVE / STEER AXLE

USE		CLIMATE
Normal		Mediterranean
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	
<b>Gearlube GL-5 80W-90</b>	<b>Unigear HS GL-3/GL-5 80W-90</b>	
<i>Change every 1000 hours/ 12 months</i>		

## TRANSMISSION Brockhouse DR.44

USE		CLIMATE
Normal		Mediterranean
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	
<b>Gear Oil Alcat 10W</b>	<b>ATF Dexron II-D</b>	
<i>Change every 1000 hours/ 12 months</i>		

## TRANSMISSION JCB

USE		CLIMATE
Normal		Mediterranean
PRODUCT RECOMMENDATION 1		
<b>ATF-F (Ford)</b>		
<i>Change every 1000 hours/ 12 months</i>		

## TRANSMISSION Powershift/ShuttleReverser/Warner

USE		CLIMATE
Normal		Mediterranean
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	
<b>Gear Oil Alcat 10W</b>	<b>ATF Dexron II-D</b>	
<i>Change every 1000 hours/ 12 months</i>		

## TRANSMISSION SYNCHROMESH Turner

USE		CLIMATE
Normal		Mediterranean
PRODUCT RECOMMENDATION 1		
<b>Multifleet SCD 20W-20</b>		
<i>Change every 1000 hours/ 12 months</i>		

# JCB TELESCOPIC HANDLERS 525-58 (1989-1994)



## HYDRAULIC SYSTEM

USE		CLIMATE
Normal		Mediterranean
PRODUCT RECOMMENDATION 1		
<b>Perlus H 32</b>		

*Change every 2000 hours/ 24 months*

## HYDRAULIC BRAKE SYSTEM

USE		CLIMATE
Normal		Mediterranean
PRODUCT RECOMMENDATION 1		
<b>Perlus H 15</b>		

*Change every 2000 hours/ 24 months*

## GREASE POINTS/NIPPLES

USE		CLIMATE
Normal		Mediterranean
PRODUCT RECOMMENDATION 1		
<b>MoS2 Grease EP 2</b>		

## GREASE POINTS/NIPPLES TELESCOPIC SLIDING SURFACES

We are unable to give a standard recommendation for this component. Please contact our service department.

## COOLING SYSTEM

USE		CLIMATE
Normal		Moderate
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	PRODUCT RECOMMENDATION 3
<b>Coolant SP 15+</b>	<b>Coolant SP 12</b>	<b>Coolant -38 Organic NF</b>

*The data mentioned in this product information sheet is meant to enable the reader to orientate himself about the properties and possible applications of our products. Although this overview is composed with all possible care on the stated date, the compiler does not accept any liability for damages caused by incompleteness and/or inaccuracies in this information, especially when these are caused by obvious typing errors. The terms of delivery of the supplier apply to all product supplies. The reader is advised, especially for critical applications, to make the final product choice in consultation with the supplier. Due to continual product research and development, the information contained herein is subject to changes without notification.*