JCB TELESCOPIC HANDLERS 531-70 (74 KW) STAGE III (2011-2013)



ENGINE JCB 444 (SF) Capacity: 12-15 liter		
USE		CLIMATE
Normal		Mediterranean
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	PRODUCT RECOMMENDATION 3
Agridiesel MSP 15W-40	Agridiesel CRD+ 15W-40	Dieselfleet CD+ 15W-40
Check every 10 hours, change every 500 h	hours/ 6 months	
USE		CLIMATE
Normal		Moderate
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	
Agrisynth LSP 10W-40	Armado Synth 10W-40	

DIFFERENTIAL FRONT Capacity: 17,7 liter	
USE	CLIMATE
Normal	Moderate
PRODUCT RECOMMENDATION 1	
Agrifluid HT	

Check every 50 hours, change every 6 months/ 500 hours

Check every 10 hours, change every 500 hours/ 6 months

DIFFERENTIAL REAR Capacity: 10 liter	
USE	CLIMATE
Normal	Moderate
PRODUCT RECOMMENDATION 1	
Agrifluid HT	
Chack avery 50 hours shangs avery 6 months/500	house

Check every 50 hours, change every 6 months/ 500 hours

HUB REDUCTIONS FRONT Capacity: 1,9 liter		
USE		CLIMATE
Normal		Moderate
PRODUCT RECOMMENDATION 1		
Agrifluid HT		
Check every 50 hours, change every 6	months/ 500 hours	

JCB TELESCOPIC HANDLERS 531-70 (74 KW) STAGE III (2011-2013)



HUB REDUCTIONS REAR Capacity: 2 liter		
USE		CLIMATE
Normal		Moderate
PRODUCT RECOMMENDATION 1		
Agrifluid HT		
Check every 50 hours, change every 6 mg	onths/ 500 hours	
TRANSMISSION Powershift Capacity: 21 liter (Change capacity), Capa	city: 23 liter (Dry fill)	
USE		CLIMATE
Normal		Mediterranean
PRODUCT RECOMMENDATION 1		
Gear Oil Alcat 30		
Check every 10 hours, change every 1000	hours/ 12 months	
use Normal		CLIMATE Moderate
PRODUCT RECOMMENDATION 1		
Gear Oil Alcat 10W		
Check every 10 hours, change every 1000) hours/ 12 months	
TRANSMISSION Synchro Shuttle SS700, Capacity: 11,5 liter (Change capacity), Capacity		
USE		CLIMATE
Normal		Mediterranean
PRODUCT RECOMMENDATION 1		
Gear Oil Alcat 30		
Check every 10 hours, change every 1000	hours/ 12 months	
USE		CLIMATE
Normal		Moderate
PRODUCT RECOMMENDATION 1		

Gear Oil Alcat 10W

Check every 10 hours, change every 1000 hours/ 12 months

JCB TELESCOPIC HANDLERS 531-70 (74 KW) STAGE III (2011-2013)



HYDRAULIC SYSTEM Capacity: 125 liter (Hydraulic tank)		
USE		CLIMATE
Normal		Tropical
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	
Perlus H 46	Perlus AF 46	
Check every 50 hours, change every 2000) hours/ 24 months	
USE		CLIMATE
Normal		Moderate
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	
Perlus H 32	Perlus AF 32	
Check every 50 hours, change every 2000) hours/ 24 months	

HYDRAULIC BRAKE SYSTEM		
USE	CLIMATE	
Normal	Moderate	
PRODUCT RECOMMENDATION 1		
Perlus H 15		
Check every 10 hours, change every 2000 hours/ 24 month		

Labora Grease	Q5 MP Calcep Grease EP 2	MP Lithep Grease EP 2
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	PRODUCT RECOMMENDATION 3
Alternative (acceptable)		Moderate
USE		CLIMATE
HT Q9 High Grade Grease		
PRODUCT RECOMMENDATION 1		
Preferred		Moderate
USE		CLIMATE
GREASE POINTS/NIPPLES		

COOLING SYSTEM Capacity: 22 liter		
USE		CLIMATE
Normal		Moderate
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	PRODUCT RECOMMENDATION 3
Coolant SP 15+	Coolant SP 12	Coolant -38 Organic NF
Chack avery 10 hours, change ave	vr. 2000 hours/24 months	'

Check every 10 hours, change every 2000 hours/24 months

The data mentioned in this product information sheet is meant to enable the reader to orientate himself about the properties and possible applications of our products. Although this overview is composed with all possible care on the stated date, the compiler does not accept any liability for damages caused by incompleteness and/or inaccuracies in this information, especially when these are caused by obvious typing errors. The terms of delivery of the supplier apply to all product supplies. The reader is advised, especially for critical applications, to make the final product choice in consultation with the supplier. Due to continual product research and development, the

PRODUCT RECOMMENDATION

JCB TELESCOPIC HANDLERS 531-70 (74 KW) STAGE III (2011-2013)



information contained herein is subject to changes without notification.