PRODUCT RECOMMENDATION

# JCB TELESCOPIC HANDLERS 535-140 HIVIZ (81 KW) STAGE IIIB/T4I (2013 AND AFTER)

**ENGINE** JCB Ecomax T4i
Capacity: 15 liter

We are unable to give a standard recommendation for this component. Please contact our service department.

**DIFFERENTIAL FRONT**
Capacity: 17,7 liter

| USE | | CLIMATE |
|---|---|---|
| Normal | | Moderate |
| PRODUCT RECOMMENDATION 1 | | |
| **Agrifluid HT** | | |

*Check every 50 hours, change every 6 months/ 500 hours*

**DIFFERENTIAL REAR**
Capacity: 17,7 liter

| USE | | CLIMATE |
|---|---|---|
| Normal | | Moderate |
| PRODUCT RECOMMENDATION 1 | | |
| **Agrifluid HT** | | |

*Check every 50 hours, change every 6 months/ 500 hours*

**HUB REDUCTIONS FRONT**
Capacity: 1,9 liter (each hub)

| USE | | CLIMATE |
|---|---|---|
| Normal | | Moderate |
| PRODUCT RECOMMENDATION 1 | | |
| **Agrifluid HT** | | |

*Check every 50 hours, change every 6 months/ 500 hours*

**HUB REDUCTIONS REAR**
Capacity: 2 liter (each hub)

| USE | | CLIMATE |
|---|---|---|
| Normal | | Moderate |
| PRODUCT RECOMMENDATION 1 | | |
| **Agrifluid HT** | | |

*Check every 50 hours, change every 6 months/ 500 hours*

KROON-OIL B.V.
Postbus 149
7600 AC Almelo

Dollegoorweg 15
7602 EC Almelo

Telefoon 0546-818165
Verkoop 0546-816184

Telefax 0546-817367

PRODUCT RECOMMENDATION

# JCB TELESCOPIC HANDLERS 535-140 HIVIZ (81 KW) STAGE IIIB/T4I (2013 AND AFTER)

**TRANSMISSION** Synchro Shuttle SS700/750
Capacity: 11,5 liter (Change capacity), Capacity: 13,5 liter (Dry fill)

| USE | | CLIMATE |
|---|---|---|
| Normal | | Mediterranean |
| PRODUCT RECOMMENDATION 1 | | |
| **Gear Oil Alcat 30** | | |
| *Check every 10 hours, change every 1000 hours/ 12 months* | | |

| USE | | CLIMATE |
|---|---|---|
| Normal | | Moderate |
| PRODUCT RECOMMENDATION 1 | | |
| **Gear Oil Alcat 10W** | | |
| *Check every 10 hours, change every 1000 hours/ 12 months* | | |

**HYDRAULIC SYSTEM**
Capacity: 127 liter (Hydraulic tank)

| USE | | CLIMATE |
|---|---|---|
| Normal | | Moderate |
| PRODUCT RECOMMENDATION 1 | PRODUCT RECOMMENDATION 2 | |
| **Perlus Biosynth 46** | **Perlus H 46** | |
| *Check every 50 hours, change every 2000 hours/ 24 months* | | |

**HYDRAULIC BRAKE SYSTEM**

| USE | | CLIMATE |
|---|---|---|
| Normal | | Moderate |
| PRODUCT RECOMMENDATION 1 | | |
| **Perlus H 15** | | |
| *Check every 10 hours, change every 2000 hours/ 24 months* | | |

**GREASE POINTS/NIPPLES**

| USE | | CLIMATE |
|---|---|---|
| Normal | | Moderate |
| PRODUCT RECOMMENDATION 1 | PRODUCT RECOMMENDATION 2 | |
| **HT Q9 High Grade Grease** | **Labora Grease** | |

KROON-OIL B.V.
Postbus 149
7600 AC Almelo

Dollegoorweg 15
7602 EC Almelo

Telefoon 0546-818165
Verkoop 0546-816184

Telefax 0546-817367

PRODUCT RECOMMENDATION

# JCB TELESCOPIC HANDLERS 535-140 HIVIZ (81 KW) STAGE IIIB/T4I (2013 AND AFTER)

**COOLING SYSTEM**
Capacity: 28 liter

| USE | CLIMATE |
|---|---|
| Normal | Moderate |

| PRODUCT RECOMMENDATION 1 | PRODUCT RECOMMENDATION 2 | PRODUCT RECOMMENDATION 3 |
|---|---|---|
| **Coolant SP 15+** | **Coolant SP 12** | **Coolant -38 Organic NF** |

*Check every 50 hours, change every 2000 hours/ 24 months*

*The data mentioned in this product information sheet is meant to enable the reader to orientate himself about the properties and possible applications of our products. Although this overview is composed with all possible care on the stated date, the compiler does not accept any liability for damages caused by incompleteness and/or inaccuracies in this information, especially when these are caused by obvious typing errors. The terms of delivery of the supplier apply to all product supplies. The reader is advised, especially for critical applications, to make the final product choice in consultation with the supplier. Due to continual product research and development, the information contained herein is subject to changes without notification.*

KROON-OIL B.V.
Postbus 149
7600 AC Almelo

Dollegoorweg 15
7602 EC Almelo

Telefoon 0546-818165
Verkoop 0546-816184

Telefax 0546-817367