

# JCB TELETRUCKS TLT30D 4WD PERKINS 404D-22 STAGE IIIA / TIER 3 (2008 AND AFTER)



**ENGINE** Perkins 404D-22  
Capacity: 10 liter

**USE**  
Normal

**CLIMATE**  
Mediterranean

**PRODUCT RECOMMENDATION 1**  
**AgriDiesel MSP 15W-40**

**PRODUCT RECOMMENDATION 2**  
**AgriDiesel CRD+ 15W-40**

**PRODUCT RECOMMENDATION 3**  
**Dieselfleet CD+ 15W-40**

**HYDRAULIC SYSTEM**  
Capacity: 55 liter

**USE**  
Normal

**CLIMATE**  
Moderate

**PRODUCT RECOMMENDATION 1**  
**AgriDiesel CRD+ 15W-40**

**PRODUCT RECOMMENDATION 2**  
**Synfleet SHPD 10W-40**

**PRODUCT RECOMMENDATION 3**  
**Dieselfleet CD+ 15W-40**

## GREASE POINTS/NIPPLES

**USE**  
Normal

**CLIMATE**  
Moderate

**PRODUCT RECOMMENDATION 1**  
**Labora Grease**

**PRODUCT RECOMMENDATION 2**  
**Q5 MP Calcep Grease EP 2**

**PRODUCT RECOMMENDATION 3**  
**MP Lithep Grease EP 2**

**COOLING SYSTEM**  
Capacity: 11 liter

**USE**  
Normal

**CLIMATE**  
Moderate

**PRODUCT RECOMMENDATION 1**  
**Coolant SP 15+**

**PRODUCT RECOMMENDATION 2**  
**Coolant SP 12**

**PRODUCT RECOMMENDATION 3**  
**Coolant -38 Organic NF**

*The data mentioned in this product information sheet is meant to enable the reader to orientate himself about the properties and possible applications of our products. Although this overview is composed with all possible care on the stated date, the compiler does not accept any liability for damages caused by incompleteness and/or inaccuracies in this information, especially when these are caused by obvious typing errors. The terms of delivery of the supplier apply to all product supplies. The reader is advised, especially for critical applications, to make the final product choice in consultation with the supplier. Due to continual product research and development, the information contained herein is subject to changes without notification.*