

# JCB VIBRATORY ROLLERS VMT160

## KUBOTA D1005 (2012 AND AFTER)



**ENGINE** Kubota D1005  
Capacity: 5,1 liter

| USE                          |                               | CLIMATE                       |
|------------------------------|-------------------------------|-------------------------------|
| Normal                       |                               | Mediterranean                 |
| PRODUCT RECOMMENDATION 1     | PRODUCT RECOMMENDATION 2      | PRODUCT RECOMMENDATION 3      |
| <b>Agridiesel MSP 15W-40</b> | <b>Agridiesel CRD+ 15W-40</b> | <b>Dieselfleet CD+ 15W-40</b> |

*Check every 10 hours, change every 250 hours/ 3 months*

| USE                          |                               | CLIMATE                       |
|------------------------------|-------------------------------|-------------------------------|
| Initial service              |                               | Mediterranean                 |
| PRODUCT RECOMMENDATION 1     | PRODUCT RECOMMENDATION 2      | PRODUCT RECOMMENDATION 3      |
| <b>Agridiesel MSP 15W-40</b> | <b>Agridiesel CRD+ 15W-40</b> | <b>Dieselfleet CD+ 15W-40</b> |

*Change every 50 hours*

### HYDRAULIC SYSTEM

Capacity: 34 liter (Hydraulic tank), Capacity: 40 liter (System)

| USE                      |                          | CLIMATE  |
|--------------------------|--------------------------|----------|
| Normal                   |                          | Tropical |
| PRODUCT RECOMMENDATION 1 | PRODUCT RECOMMENDATION 2 |          |
| <b>Perlus H 68</b>       | <b>Perlus AF 68</b>      |          |

*Check every 10 hours, change every 2000 hours/ 24 months*

| USE                      |                          | CLIMATE  |
|--------------------------|--------------------------|----------|
| Normal                   |                          | Moderate |
| PRODUCT RECOMMENDATION 1 | PRODUCT RECOMMENDATION 2 |          |
| <b>Perlus H 46</b>       | <b>Perlus AF 46</b>      |          |

*Check every 10 hours, change every 2000 hours/ 24 months*

### GREASE POINTS/NIPPLES

| USE                            |                          | CLIMATE  |
|--------------------------------|--------------------------|----------|
| Normal                         |                          | Moderate |
| PRODUCT RECOMMENDATION 1       | PRODUCT RECOMMENDATION 2 |          |
| <b>HT Q9 High Grade Grease</b> | <b>Labora Grease</b>     |          |

# JCB VIBRATORY ROLLERS VMT160

## KUBOTA D1005 (2012 AND AFTER)

**COOLING SYSTEM**

Capacity: 6 liter

| USE                      |                          | CLIMATE                       |
|--------------------------|--------------------------|-------------------------------|
| Normal                   |                          | Moderate                      |
| PRODUCT RECOMMENDATION 1 | PRODUCT RECOMMENDATION 2 | PRODUCT RECOMMENDATION 3      |
| <b>Coolant SP 15+</b>    | <b>Coolant SP 12</b>     | <b>Coolant -38 Organic NF</b> |

*Check every 10 hours, change every 2000 hours/ 24 months*

**VIBRATORY SYSTEM**

Capacity: 1,1 liter (1000 mm), Capacity: 0,7 liter (800 mm), Capacity: 0,9 liter (900 mm)

| USE                      |  | CLIMATE  |
|--------------------------|--|----------|
| Normal                   |  | Moderate |
| PRODUCT RECOMMENDATION 1 |  |          |
| <b>Abacot MEP 100</b>    |  |          |

*Check every 6 months/ 500 hours, change every 24 months/ 2000 hours*

| USE                      |  | CLIMATE  |
|--------------------------|--|----------|
| Initial service          |  | Moderate |
| PRODUCT RECOMMENDATION 1 |  |          |
| <b>Abacot MEP 100</b>    |  |          |

*Change every 500 hours/ 12 months*

*The data mentioned in this product information sheet is meant to enable the reader to orientate himself about the properties and possible applications of our products. Although this overview is composed with all possible care on the stated date, the compiler does not accept any liability for damages caused by incompleteness and/or inaccuracies in this information, especially when these are caused by obvious typing errors. The terms of delivery of the supplier apply to all product supplies. The reader is advised, especially for critical applications, to make the final product choice in consultation with the supplier. Due to continual product research and development, the information contained herein is subject to changes without notification.*