

**JLG BOOM LIFTS ELECTRIC E E600JP****HYDRAULIC SYSTEM**

Capacity: 60,2 liter (Serial Number &lt;51941), Capacity: 46,9 liter (Serial Number &gt;51941)

USE	CLIMATE
Normal	Moderate

## PRODUCT RECOMMENDATION 1

**Perlus H 15***Change every 1200 hours/ 24 months***SWING BEARING**

USE	CLIMATE
Normal	Moderate

## PRODUCT RECOMMENDATION 1

**Labora Grease**

## PRODUCT RECOMMENDATION 2

**Q5 MP Calcep Grease EP 2**

## PRODUCT RECOMMENDATION 3

**MP Lithep Grease EP 2***Change every 3 months/ 150 hours***SWING DRIVE HUB**

Capacity: 0,7 liter

USE	CLIMATE
Normal	Moderate

## PRODUCT RECOMMENDATION 1

**Gearlube GL-5 80W-90**

## PRODUCT RECOMMENDATION 2

**Unigear HS GL-3/GL-5 80W-90***Check every 3 months/ 150 hours, change every 24 months/ 1200 hours***WHEEL TORQUE HUB**

USE	CLIMATE
Normal	Moderate

## PRODUCT RECOMMENDATION 1

**Gearlube GL-5 80W-90**

## PRODUCT RECOMMENDATION 2

**Unigear HS GL-3/GL-5 80W-90***Check every 3 months/ 150 hours, change every 24 months/ 1200 hours*

The data mentioned in this product information sheet is meant to enable the reader to orientate himself about the properties and possible applications of our products. Although this overview is composed with all possible care on the stated date, the compiler does not accept any liability for damages caused by incompleteness and/or inaccuracies in this information, especially when these are caused by obvious typing errors. The terms of delivery of the supplier apply to all product supplies. The reader is advised, especially for critical applications, to make the final product choice in consultation with the supplier. Due to continual product research and development, the information contained herein is subject to changes without notification.