## JLG BOOM LIFTS WITH INTERNAL COMBUSTION ENGINE 40H DEUTZ F3L912



	CLIMATE
	Mediterranean
PRODUCT RECOMMENDATION 2	
Multifleet SHPD 15W-40	

Check every 10 hours, change every 3 months/ 150 hours

USE		CLIMATE
Normal		Moderate
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	PRODUCT RECOMMENDATION 3
Kroontrak MTH 10W-30	Synfleet SHPD 10W-40	Multifleet SHPD 10W-40

Check every 10 hours, change every 3 months/ 150 hours

HYDRAULIC SYSTEM Capacity: 104 liter (Reservoir), Capacity: 265 liter (System)		
USE		CLIMATE
Normal		Moderate
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	PRODUCT RECOMMENDATION 3
Agrifluid Synth XHP Ultra	Agrifluid HT-Plus	Kroontrak MTH 10W-30
Check every 10 hours, change every	1200 hours/ 24 months	

SWING BEARING		
USE		CLIMATE
Normal		Moderate
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	PRODUCT RECOMMENDATION 3
Labora Grease	Q5 MP Calcep Grease EP 2	MP Lithep Grease EP 2
Change every 100 hours		

LIMATE
Moderate
RODUCT RECOMMENDATION 3
IP Lithep Grease EP 2
1

## JLG BOOM LIFTS WITH INTERNAL COMBUSTION ENGINE 40H DEUTZ F3L912



SWING REDUCTION UNIT Capacity: 1,2 liter		
USE		CLIMATE
Normal		Moderate
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	
Gearlube GL-5 80W-90	Unigear HS GL-3/GL-5 80W-90	

Check every 50 hours, change every 1200 hours/24 months

WHEEL BEARINGS		
USE		CLIMATE
Normal		Moderate
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	PRODUCT RECOMMENDATION 3
Labora Grease	Q5 MP Calcep Grease EP 2	MP Lithep Grease EP 2
Change every 500 hours		'

WHEEL DRIVE HUB
Capacity: 1,2 liter (each hub)

USE

Normal

PRODUCT RECOMMENDATION 1

Gearlube GL-5 80W-90

Check every 50 hours, change every 1200 hours/ 24 months

The data mentioned in this product information sheet is meant to enable the reader to orientate himself about the properties and possible applications of our products. Although this overview is composed with all possible care on the stated date, the compiler does not accept any liability for damages caused by incompleteness and/or inaccuracies in this information, especially when these are caused by obvious typing errors. The terms of delivery of the supplier apply to all product supplies. The reader is advised, especially for critical applications, to make the final product choice in consultation with the supplier. Due to continual product research and development, the information contained herein is subject to changes without notification.