

JLG BOOM LIFTS WITH INTERNAL COMBUSTION ENGINE 600A DEUTZ F4M2011

**ENGINE** Deutz F4M-2011

Capacity: 4,73 liter (Cooler), Capacity: 10,5 liter (Engine only), Capacity: 15,23 liter (Total)

USE	CLIMATE
Normal	Mediterranean

PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	
HDX 20W-50	Multifleet SHPD 20W-50	

Change every 3 months/ 150 hours

USE	CLIMATE
Normal	Moderate

PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	PRODUCT RECOMMENDATION 3
Kroontrak MTH 10W-30	Synfleet SHPD 10W-40	Dieselfleet CD+ 15W-40

*Change every 3 months/ 150 hours***HYDRAULIC SYSTEM**

Capacity: 140,8 liter (Hydraulic system including tank), Capacity: 117,3 liter (Hydraulic tank)

USE	CLIMATE
Normal	Moderate

PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	PRODUCT RECOMMENDATION 3
Agrifluid HT-Plus	Kroontrak MTH 10W-30	Agrifluid HT

*Change every 1200 hours/ 24 months***COOLING SYSTEM**

USE	CLIMATE
Normal	Moderate

PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	
Coolant -38 Organic NF	Coolant -26	

SPINDLE/BUSHING

USE	CLIMATE
Normal	Moderate

PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	PRODUCT RECOMMENDATION 3
Labora Grease	Q5 MP Calcep Grease EP 2	MP Lithep Grease EP 2

Change every 3 months/ 150 hours

JLG BOOM LIFTS WITH INTERNAL COMBUSTION ENGINE 600A DEUTZ F4M2011



SWING BEARING

USE Normal		CLIMATE Moderate
PRODUCT RECOMMENDATION 1 Labora Grease	PRODUCT RECOMMENDATION 2 Q5 MP Calcep Grease EP 2	PRODUCT RECOMMENDATION 3 MP Lithep Grease EP 2

Change every 3 months/ 150 hours

SWING REDUCTION UNIT

Capacity: 0,5 liter

USE Normal		CLIMATE Moderate
PRODUCT RECOMMENDATION 1 Gearlube GL-5 80W-90	PRODUCT RECOMMENDATION 2 Unigear HS GL-3/GL-5 80W-90	

Check every 3 months/ 150 hours, change every 24 months/ 1200 hours

WHEEL BEARINGS

USE Normal		CLIMATE Moderate
PRODUCT RECOMMENDATION 1 Labora Grease	PRODUCT RECOMMENDATION 2 Q5 MP Calcep Grease EP 2	PRODUCT RECOMMENDATION 3 MP Lithep Grease EP 2

Change every 1200 hours/ 24 months

WHEEL DRIVE HUB

Capacity: 0,5 liter (each hub)

USE Normal		CLIMATE Moderate
PRODUCT RECOMMENDATION 1 Gearlube GL-5 80W-90	PRODUCT RECOMMENDATION 2 Unigear HS GL-3/GL-5 80W-90	

Check every 3 months/ 150 hours, change every 24 months/ 1200 hours

The data mentioned in this product information sheet is meant to enable the reader to orientate himself about the properties and possible applications of our products. Although this overview is composed with all possible care on the stated date, the compiler does not accept any liability for damages caused by incompleteness and/or inaccuracies in this information, especially when these are caused by obvious typing errors. The terms of delivery of the supplier apply to all product supplies. The reader is advised, especially for critical applications, to make the final product choice in consultation with the supplier. Due to continual product research and development, the information contained herein is subject to changes without notification.