

# JLG BOOM LIFTS WITH INTERNAL COMBUSTION ENGINE 600AJ DEUTZ F4M1011F

**ENGINE** Deutz F4M-1011F

Capacity: 4,5 liter (Cooler), Capacity: 10,5 liter (Engine only), Capacity: 15 liter (Total)

USE	CLIMATE
Normal	Mediterranean

PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	
<b>HDX 20W-50</b>	<b>Multifleet SHPD 20W-50</b>	

*Change every 3 months/ 150 hours*

USE	CLIMATE
Normal	Moderate

PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	PRODUCT RECOMMENDATION 3
<b>Kroontrak MTH 10W-30</b>	<b>Synfleet SHPD 10W-40</b>	<b>Dieselfleet CD+ 15W-40</b>

*Change every 3 months/ 150 hours***HYDRAULIC SYSTEM**

Capacity: 116 liter

USE	CLIMATE
Normal	Moderate

PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	PRODUCT RECOMMENDATION 3
<b>Agrifluid HT-Plus</b>	<b>Kroontrak MTH 10W-30</b>	<b>Agrifluid HT</b>

*Change every 1200 hours/ 24 months***COOLING SYSTEM**

Capacity: 4,5 liter

USE	CLIMATE
Normal	Moderate

PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	
<b>Coolant -38 Organic NF</b>	<b>Coolant -26</b>	

**SPINDLE/BUSHING**

USE	CLIMATE
Normal	Moderate

PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	PRODUCT RECOMMENDATION 3
<b>Labora Grease</b>	<b>Q5 MP Calcep Grease EP 2</b>	<b>MP Lithep Grease EP 2</b>

*Change every 3 months/ 150 hours*

# JLG BOOM LIFTS WITH INTERNAL COMBUSTION ENGINE 600AJ DEUTZ F4M1011F



## SWING BEARING

USE Normal		CLIMATE Moderate
PRODUCT RECOMMENDATION 1 <b>Labora Grease</b>	PRODUCT RECOMMENDATION 2 <b>Q5 MP Calcep Grease EP 2</b>	PRODUCT RECOMMENDATION 3 <b>MP Lithep Grease EP 2</b>

*Change every 3 months/ 150 hours*

## SWING REDUCTION UNIT

Capacity: 0,5 liter

USE Normal		CLIMATE Moderate
PRODUCT RECOMMENDATION 1 <b>Gearlube GL-5 80W-90</b>	PRODUCT RECOMMENDATION 2 <b>Unigear HS GL-3/GL-5 80W-90</b>	

*Check every 3 months/ 150 hours, change every 24 months/ 1200 hours*

## WHEEL BEARINGS

USE Normal		CLIMATE Moderate
PRODUCT RECOMMENDATION 1 <b>Labora Grease</b>	PRODUCT RECOMMENDATION 2 <b>Q5 MP Calcep Grease EP 2</b>	PRODUCT RECOMMENDATION 3 <b>MP Lithep Grease EP 2</b>

*Change every 1200 hours/ 24 months*

## WHEEL DRIVE HUB

Capacity: 0,5 liter (each hub)

USE Normal		CLIMATE Moderate
PRODUCT RECOMMENDATION 1 <b>Gearlube GL-5 80W-90</b>	PRODUCT RECOMMENDATION 2 <b>Unigear HS GL-3/GL-5 80W-90</b>	

*Check every 3 months/ 150 hours, change every 24 months/ 1200 hours*

*The data mentioned in this product information sheet is meant to enable the reader to orientate himself about the properties and possible applications of our products. Although this overview is composed with all possible care on the stated date, the compiler does not accept any liability for damages caused by incompleteness and/or inaccuracies in this information, especially when these are caused by obvious typing errors. The terms of delivery of the supplier apply to all product supplies. The reader is advised, especially for critical applications, to make the final product choice in consultation with the supplier. Due to continual product research and development, the information contained herein is subject to changes without notification.*