

JLG BOOM LIFTS WITH INTERNAL COMBUSTION ENGINE 600AJ FORD LRG-423

**ENGINE** Ford LRG-423

Capacity: 4,73 liter, Filter capacity: 0,95 liter

USE	CLIMATE
Normal	Moderate

PRODUCT RECOMMENDATION 1

Kroontrak MTH 10W-30*Change every 3 months/ 150 hours*

USE	CLIMATE
Normal	Arctic

PRODUCT RECOMMENDATION 1

Asyntho 5W-30*Change every 3 months/ 150 hours***HYDRAULIC SYSTEM**

Capacity: 140,8 liter (Hydraulic system including tank), Capacity: 117,3 liter (Hydraulic tank)

USE	CLIMATE
Normal	Moderate

PRODUCT RECOMMENDATION 1

Agrifluid HT-Plus

PRODUCT RECOMMENDATION 2

Kroontrak MTH 10W-30

PRODUCT RECOMMENDATION 3

Agrifluid HT*Change every 1200 hours/ 24 months***COOLING SYSTEM**

USE	CLIMATE
Normal	Moderate

PRODUCT RECOMMENDATION 1

Coolant -38 Organic NF

PRODUCT RECOMMENDATION 2

Coolant -26**SPINDLE/BUSHING**

USE	CLIMATE
Normal	Moderate

PRODUCT RECOMMENDATION 1

Labora Grease

PRODUCT RECOMMENDATION 2

Q5 MP Calcep Grease EP 2

PRODUCT RECOMMENDATION 3

MP Lithep Grease EP 2*Change every 3 months/ 150 hours*

JLG BOOM LIFTS WITH INTERNAL COMBUSTION ENGINE 600AJ FORD LRG-423



SWING BEARING

USE Normal		CLIMATE Moderate
PRODUCT RECOMMENDATION 1 Labora Grease	PRODUCT RECOMMENDATION 2 Q5 MP Calcep Grease EP 2	PRODUCT RECOMMENDATION 3 MP Lithep Grease EP 2

Change every 3 months/ 150 hours

SWING REDUCTION UNIT

Capacity: 0,5 liter

USE Normal		CLIMATE Moderate
PRODUCT RECOMMENDATION 1 Gearlube GL-5 80W-90	PRODUCT RECOMMENDATION 2 Unigear HS GL-3/GL-5 80W-90	

Check every 3 months/ 150 hours, change every 24 months/ 1200 hours

WHEEL BEARINGS

USE Normal		CLIMATE Moderate
PRODUCT RECOMMENDATION 1 Labora Grease	PRODUCT RECOMMENDATION 2 Q5 MP Calcep Grease EP 2	PRODUCT RECOMMENDATION 3 MP Lithep Grease EP 2

Change every 1200 hours/ 24 months

WHEEL DRIVE HUB

Capacity: 0,5 liter (each hub)

USE Normal		CLIMATE Moderate
PRODUCT RECOMMENDATION 1 Gearlube GL-5 80W-90	PRODUCT RECOMMENDATION 2 Unigear HS GL-3/GL-5 80W-90	

Check every 3 months/ 150 hours, change every 24 months/ 1200 hours

The data mentioned in this product information sheet is meant to enable the reader to orientate himself about the properties and possible applications of our products. Although this overview is composed with all possible care on the stated date, the compiler does not accept any liability for damages caused by incompleteness and/or inaccuracies in this information, especially when these are caused by obvious typing errors. The terms of delivery of the supplier apply to all product supplies. The reader is advised, especially for critical applications, to make the final product choice in consultation with the supplier. Due to continual product research and development, the information contained herein is subject to changes without notification.