PRODUCT RECOMMENDATION

# JLG BOOM LIFTS WITH INTERNAL COMBUSTION ENGINE 600SJ FORD LRG-425 80000 >

**ENGINE** Ford LRG-425
Capacity: 4,25 liter

| USE | CLIMATE |
|---|---|
| Normal | Moderate |

| PRODUCT RECOMMENDATION 1 | PRODUCT RECOMMENDATION 2 | PRODUCT RECOMMENDATION 3 |
|---|---|---|
| **Kroontrak CVT 10W-40** | **Kroontrak MTH 10W-30** | **Multifleet SHPD 10W-40** |

*Change every 3 months/ 150 hours*

**HUB REDUCTIONS FRONT**
Capacity: 0,5 liter (each hub)

| USE | CLIMATE |
|---|---|
| Normal | Moderate |

| PRODUCT RECOMMENDATION 1 | PRODUCT RECOMMENDATION 2 |
|---|---|
| **Gearlube GL-5 80W-90** | **Unigear HS GL-3/GL-5 80W-90** |

*Check every 3 months/ 150 hours, change every 24 months/ 1200 hours*

**HUB REDUCTIONS REAR**
Capacity: 0,5 liter (each hub)

| USE | CLIMATE |
|---|---|
| Normal | Moderate |

| PRODUCT RECOMMENDATION 1 | PRODUCT RECOMMENDATION 2 |
|---|---|
| **Gearlube GL-5 80W-90** | **Unigear HS GL-3/GL-5 80W-90** |

*Check every 3 months/ 150 hours, change every 24 months/ 1200 hours*

**HYDRAULIC SYSTEM**
Capacity: 140,8 liter (System), Capacity: 117,3 liter (Tank)

| USE | CLIMATE |
|---|---|
| Normal | Moderate |

| PRODUCT RECOMMENDATION 1 | PRODUCT RECOMMENDATION 2 | PRODUCT RECOMMENDATION 3 |
|---|---|---|
| **Agrifluid Synth XHP Ultra** | **Agrifluid HT-Plus** | **Kroontrak MTH 10W-30** |

*Change every 1200 hours/ 24 months*

**GREASE POINTS/NIPPLES**

| USE | CLIMATE |
|---|---|
| Normal | Moderate |

| PRODUCT RECOMMENDATION 1 | PRODUCT RECOMMENDATION 2 | PRODUCT RECOMMENDATION 3 |
|---|---|---|
| **Labora Grease** | **Q5 MP Calcep Grease EP 2** | **MP Lithep Grease EP 2** |

*Change every 6 months/ 300 hours*

KROON-OIL B.V.
Postbus 149
7600 AC Almelo

Dollegoorweg 15
7602 EC Almelo

Telefoon 0546-818165
Verkoop 0546-816184

Telefax 0546-817367

PRODUCT RECOMMENDATION

# JLG BOOM LIFTS WITH INTERNAL COMBUSTION ENGINE 600SJ FORD LRG-425 80000 >

## COOLING SYSTEM
Capacity: 15 liter

| USE | CLIMATE |
|---|---|
| Normal | Moderate |

| PRODUCT RECOMMENDATION 1 | PRODUCT RECOMMENDATION 2 | |
|---|---|---|
| **Coolant -38 Organic NF** | **Coolant -26** | |

## SWING BEARING

| USE | CLIMATE |
|---|---|
| Normal | Moderate |

| PRODUCT RECOMMENDATION 1 | PRODUCT RECOMMENDATION 2 | PRODUCT RECOMMENDATION 3 |
|---|---|---|
| **Labora Grease** | **Q5 MP Calcep Grease EP 2** | **MP Lithep Grease EP 2** |

*Check every 3 months/ 150 hours*

## WHEEL BEARINGS

| USE | CLIMATE |
|---|---|
| Normal | Moderate |

| PRODUCT RECOMMENDATION 1 | PRODUCT RECOMMENDATION 2 | PRODUCT RECOMMENDATION 3 |
|---|---|---|
| **Labora Grease** | **Q5 MP Calcep Grease EP 2** | **MP Lithep Grease EP 2** |

*Change every 1200 hours/ 24 months*

*The data mentioned in this product information sheet is meant to enable the reader to orientate himself about the properties and possible applications of our products. Although this overview is composed with all possible care on the stated date, the compiler does not accept any liability for damages caused by incompleteness and/or inaccuracies in this information, especially when these are caused by obvious typing errors. The terms of delivery of the supplier apply to all product supplies. The reader is advised, especially for critical applications, to make the final product choice in consultation with the supplier. Due to continual product research and development, the information contained herein is subject to changes without notification.*

KROON-OIL B.V.
Postbus 149
7600 AC Almelo

Dollegoorweg 15
7602 EC Almelo

Telefoon 0546-818165
Verkoop 0546-816184

Telefax 0546-817367