

**JLG SCISSOR LIFTS, ELECTRIC 2658E3****HYDRAULIC SYSTEM**

Capacity: 22 liter (System), Capacity: 12,7 liter (Tank)

USE		CLIMATE
Normal		Moderate
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	PRODUCT RECOMMENDATION 3
<b>Agrifluid Synth XHP Ultra</b>	<b>Agrifluid HT-Plus</b>	<b>Kroontrak MTH 10W-30</b>

*Check every 8 hours, change every 800 hours***KINGPIN HOUSING**

USE		CLIMATE
Normal		Moderate
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	PRODUCT RECOMMENDATION 3
<b>Labora Grease</b>	<b>Q5 MP Calcep Grease EP 2</b>	<b>MP Lithep Grease EP 2</b>

*Change every 100 hours***WHEEL BEARINGS**

USE		CLIMATE
Normal		Moderate
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	PRODUCT RECOMMENDATION 3
<b>Labora Grease</b>	<b>Q5 MP Calcep Grease EP 2</b>	<b>MP Lithep Grease EP 2</b>

*Change every 800 hours*

The data mentioned in this product information sheet is meant to enable the reader to orientate himself about the properties and possible applications of our products. Although this overview is composed with all possible care on the stated date, the compiler does not accept any liability for damages caused by incompleteness and/or inaccuracies in this information, especially when these are caused by obvious typing errors. The terms of delivery of the supplier apply to all product supplies. The reader is advised, especially for critical applications, to make the final product choice in consultation with the supplier. Due to continual product research and development, the information contained herein is subject to changes without notification.