PRODUCT RECOMMENDATION

JLG SCISSOR LIFTS, WITH INTERNAL COMBUSTION ENGINE 4394RT GM 3.0 (3000CC)

ENGINE GM 3.0
Capacity: 4,25 liter

USE	CLIMATE
Normal	Moderate

PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	PRODUCT RECOMMENDATION 3
Kroontrak MTH 10W-30	**Synfleet SHPD 10W-40**	**Multifleet SHPD 10W-40**

Change every 3 months/ 150 hours

TRANSMISSION

USE	CLIMATE
Normal	Moderate

PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	
Gearlube GL-5 80W-90	**Unigear HS GL-3/GL-5 80W-90**	

Check every 6 months, change every 12 months/ 1500 hours

USE	CLIMATE
Initial service	Moderate

PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	
Gearlube GL-5 80W-90	**Unigear HS GL-3/GL-5 80W-90**	

Change every 150 hours

HYDRAULIC SYSTEM
Capacity: 151 liter

USE	CLIMATE
Normal	Moderate

PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	PRODUCT RECOMMENDATION 3
Agrifluid Synth XHP Ultra	**Agrifluid HT-Plus**	**Kroontrak MTH 10W-30**

Check every 10 hours, change every 1200 hours/ 24 months

GREASE POINTS/NIPPLES

USE	CLIMATE
Normal	Moderate

PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	PRODUCT RECOMMENDATION 3
Labora Grease	**Q5 MP Calcep Grease EP 2**	**MP Lithep Grease EP 2**

Change every 1200 hours/ 24 months

KROON-OIL B.V.
Postbus 149
7600 AC Almelo

Dollegoorweg 15
7602 EC Almelo

Telefoon 0546-818165
Verkoop 0546-816184

Telefax 0546-817367

PRODUCT RECOMMENDATION

JLG SCISSOR LIFTS, WITH INTERNAL COMBUSTION ENGINE 4394RT GM 3.0 (3000CC)

COOLING SYSTEM
Capacity: 0-0 liter (Between min and max.)

USE	CLIMATE
Normal	Moderate

PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	
Coolant -38 Organic NF	**Coolant -26**	

The data mentioned in this product information sheet is meant to enable the reader to orientate himself about the properties and possible applications of our products. Although this overview is composed with all possible care on the stated date, the compiler does not accept any liability for damages caused by incompleteness and/or inaccuracies in this information, especially when these are caused by obvious typing errors. The terms of delivery of the supplier apply to all product supplies. The reader is advised, especially for critical applications, to make the final product choice in consultation with the supplier. Due to continual product research and development, the information contained herein is subject to changes without notification.

KROON-OIL B.V.
Postbus 149
7600 AC Almelo

Dollegoorweg 15
7602 EC Almelo

Telefoon 0546-818165
Verkoop 0546-816184

Telefax 0546-817367