

# JLG SCISSOR LIFTS, WITH INTERNAL COMBUSTION ENGINE CM40RT FORD VSG-411

**ENGINE** Ford VSG-411

Capacity: 3,3 liter, Filter capacity: 0,5 liter

USE	CLIMATE
Normal	Mediterranean

## PRODUCT RECOMMENDATION 1

**HDX 20W-50**

## PRODUCT RECOMMENDATION 2

**Multifleet SHPD 15W-40***Check every 10 hours*

USE	CLIMATE
Normal	Moderate

## PRODUCT RECOMMENDATION 1

**Kroontrak CVT 10W-40**

## PRODUCT RECOMMENDATION 2

**Kroontrak MTH 10W-30***Check every 10 hours*

USE	CLIMATE
Normal	Cold

## PRODUCT RECOMMENDATION 1

**Asyntho 5W-30***Check every 10 hours***HYDRAULIC SYSTEM**

Capacity: 91 liter (System), Capacity: 76 liter (Tank)

USE	CLIMATE
Normal	Moderate

## PRODUCT RECOMMENDATION 1

**Agrifluid Synth XHP Ultra**

## PRODUCT RECOMMENDATION 2

**Agrifluid HT-Plus**

## PRODUCT RECOMMENDATION 3

**Kroontrak MTH 10W-30***Check every 10 hours, change every 2000 hours***GREASE POINTS/NIPPLES**

USE	CLIMATE
Normal	Moderate

## PRODUCT RECOMMENDATION 1

**Labora Grease**

## PRODUCT RECOMMENDATION 2

**Q5 MP Calcep Grease EP 2**

## PRODUCT RECOMMENDATION 3

**MP Lithep Grease EP 2***Change every 50 hours*

# JLG SCISSOR LIFTS, WITH INTERNAL COMBUSTION ENGINE CM40RT FORD VSG-411



## COOLING SYSTEM

Capacity: 13,3 liter

USE		CLIMATE
Normal		Moderate
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	
<b>Coolant -38 Organic NF</b>	<b>Coolant -26</b>	

## STEER SPINDLE

USE		CLIMATE
Normal		Moderate
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	PRODUCT RECOMMENDATION 3
<b>Labora Grease</b>	<b>Q5 MP Calcep Grease EP 2</b>	<b>MP Lithep Grease EP 2</b>

*Change every 50 hours*

## WHEEL BEARINGS

USE		CLIMATE
Normal		Moderate
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	PRODUCT RECOMMENDATION 3
<b>Labora Grease</b>	<b>Q5 MP Calcep Grease EP 2</b>	<b>MP Lithep Grease EP 2</b>

*Change every 2000 hours*

## WHEEL TORQUE HUB

Capacity: 0,3 kg (each hub)

USE		CLIMATE
Normal		Moderate
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	
<b>Gearlube GL-5 80W-90</b>	<b>Unigear HS GL-3/GL-5 80W-90</b>	

*Change every 500 hours*

The data mentioned in this product information sheet is meant to enable the reader to orientate himself about the properties and possible applications of our products. Although this overview is composed with all possible care on the stated date, the compiler does not accept any liability for damages caused by incompleteness and/or inaccuracies in this information, especially when these are caused by obvious typing errors. The terms of delivery of the supplier apply to all product supplies. The reader is advised, especially for critical applications, to make the final product choice in consultation with the supplier. Due to continual product research and development, the information contained herein is subject to changes without notification.