## JLG TELEHANDLERS 4012 PERKINS 1004-42 (<- 1160000358)



<b>ENGINE</b> Perkins 1004-42 Capacity: 8,5 liter			
USE		CLIMATE	
Normal		Moderate	
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2		
Dieselfleet CD+ 15W-40	Multifleet SHPD 15W-40		
Check every 10 hours, change every	y 250 hours		
USE		CLIMATE	
Initial service		Moderate	
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2		
Dieselfleet CD+ 15W-40	Multifleet SHPD 15W-40		
Check every 10 hours, change every	y 50 hours		

DIFFERENTIAL FRONT Capacity: 7,3 liter			
USE		CLIMATE	
Normal		Moderate	
PRODUCT RECOMMENDATION 1			
Agrifluid HT-Plus			
Check every 250 hours, change every 10	00 hours		
USE		CLIMATE	
Initial service		Moderate	
PRODUCT RECOMMENDATION 1			

PRODUCT RECOMMENDATION 1

Agrifluid HT-Plus

Change every 50 hours

<b>DIFFERENTIAL REAR</b> Capacity: 7,3 liter		
USE		CLIMATE
Normal		Moderate
PRODUCT RECOMMENDATION 1		
Agrifluid HT-Plus		
Check every 250 hours, change eve	ry 1000 hours	'

USE	CLIMATE
Initial service	Moderate
PRODUCT RECOMMENDATION 1	
Agrifluid HT-Plus	
Change every 50 hours	

## JLG TELEHANDLERS 4012 PERKINS 1004-42 (<- 1160000358)



TRANSFERBOX Capacity: 1,4 liter		
USE		CLIMATE
Normal		Moderate
PRODUCT RECOMMENDATION 1		
Agrifluid HT-Plus		
Check every 250 hours, change every 10	00 hours	
USE		CLIMATE
Initial service		Moderate
PRODUCT RECOMMENDATION 1		
Agrifluid HT-Plus		
Change every 50 hours		
TRANSMISSION POWERSHIFT Dana		

Capacity: 12,9 liter		
USE		CLIMATE
Normal		Moderate
PRODUCT RECOMMENDATION 1		
Agrifluid HT-Plus		
Check every 8 hours, change every 1000	hours	
USE		CLIMATE
Initial service		Moderate
PRODUCT RECOMMENDATION 1		
Agrifluid HT-Plus		
Change every 50 hours		

HYDRAULIC SYSTEM Capacity: 160 liter (Hydraulic tank), Capacity: 246 liter (System)			
USE		CLIMATE	
Normal		Moderate	
PRODUCT RECOMMENDATION 1			
Agrifluid HT-Plus			
Check every 10 hours, change every 1500 hours			

## JLG TELEHANDLERS 4012 PERKINS 1004-42 (<- 1160000358)



COOLING SYSTEM Capacity: 19,7 liter			
USE		CLIMATE	
Normal		Moderate	
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2		
Coolant -38 Organic NF	Coolant -26		
Check every 10 hours, change every 1500 hours			

WHEEL DRIVE HUB Capacity: 1,4 liter (each hub)	
USE	CLIMATE
Normal	Moderate
PRODUCT RECOMMENDATION 1	
Agrifluid HT-Plus	

Check every 250 hours, change every 1000 hours

USE	CLIMATE
Initial service	Moderate
PRODUCT RECOMMENDATION 1	
Agrifluid HT-Plus	

Change every 50 hours

The data mentioned in this product information sheet is meant to enable the reader to orientate himself about the properties and possible applications of our products. Although this overview is composed with all possible care on the stated date, the compiler does not accept any liability for damages caused by incompleteness and/or inaccuracies in this information, especially when these are caused by obvious typing errors. The terms of delivery of the supplier apply to all product supplies. The reader is advised, especially for critical applications, to make the final product choice in consultation with the supplier. Due to continual product research and development, the information contained herein is subject to changes without notification.