JLG TELEHANDLERS 4017 PERKINS 1004-40T



| ENGINE Perkins 1004-40T Capacity: 8,5 liter | | | |
|--|--------------------------|----------|--|
| USE | | CLIMATE | |
| Normal | | Moderate | |
| PRODUCT RECOMMENDATION 1 | PRODUCT RECOMMENDATION 2 | | |
| Dieselfleet CD+ 15W-40 | Multifleet SHPD 15W-40 | | |
| Check every 10 hours, change every | 250 hours | | |
| USE | | CLIMATE | |
| Initial service | | Moderate | |
| PRODUCT RECOMMENDATION 1 | PRODUCT RECOMMENDATION 2 | | |
| Dieselfleet CD+ 15W-40 | Multifleet SHPD 15W-40 | | |
| Check every 10 hours, change every | , 50 hours | | |

| DIFFERENTIAL FRONT Capacity: 7,3 liter | | |
|--|--|----------|
| USE | | CLIMATE |
| Normal | | Moderate |
| PRODUCT RECOMMENDATION 1 | | |
| Agrifluid HT-Plus | | |
| Check every 250 hours, change every 1000 hours | | |
| USE | | CLIMATE |
| Initial service | | Moderate |
| PRODUCT RECOMMENDATION 1 | | |
| Agrifluid HT-Plus | | |

| DIFFERENTIAL REAR Capacity: 7,3 liter | | |
|---|----------|----------|
| USE | | CLIMATE |
| Normal | | Moderate |
| PRODUCT RECOMMENDATION 1 | | |
| Agrifluid HT-Plus | | |
| Check every 250 hours, change every 100 | 00 hours | |
| USE | | CLIMATE |
| Initial service | | Moderate |
| PRODUCT RECOMMENDATION 1 | | |
| Agrifluid HT-Plus | | |
| Change every 50 hours | | |

Change every 50 hours

JLG TELEHANDLERS 4017 PERKINS 1004-40T



| TRANSFERBOX Capacity: 1,4 liter | | |
|--|--|----------|
| USE | | CLIMATE |
| Normal | | Moderate |
| PRODUCT RECOMMENDATION 1 | | |
| Agrifluid HT-Plus | | |
| Check every 250 hours, change every 1000 hours | | |
| USE | | CLIMATE |
| Initial service | | Moderate |
| PRODUCT RECOMMENDATION 1 | | |
| Agrifluid HT-Plus | | |
| Change every 50 hours | | |

| USE | CLIMATE |
|--|----------|
| Normal | Moderate |
| PRODUCT RECOMMENDATION 1 | |
| Agrifluid HT-Plus | |
| Check every 8 hours, change every 1000 hours | |
| USE | CLIMATE |
| Initial service | Moderate |
| PRODUCT RECOMMENDATION 1 | |
| Agrifluid HT-Plus | |

| HYDRAULIC SYSTEM Capacity: 160 liter (Hydraulic tank), Capacity: 220 liter (System) | | |
|---|--|----------|
| USE | | CLIMATE |
| Normal | | Moderate |
| PRODUCT RECOMMENDATION 1 | | |
| Agrifluid HT-Plus | | |
| Check every 10 hours, change every 1500 hours | | |

JLG TELEHANDLERS 4017 PERKINS 1004-40T



| COOLING SYSTEM Capacity: 19,7 liter | | |
|---------------------------------------|--------------------------|----------|
| USE | | CLIMATE |
| Normal | | Moderate |
| PRODUCT RECOMMENDATION 1 | PRODUCT RECOMMENDATION 2 | |
| Coolant -38 Organic NF | Coolant -26 | |
| Check every 10 hours, change every 15 | 20 hours | |

Check every 10 hours, change every 1500 hours

| WHEEL DRIVE HUB Capacity: 1,4 liter (each hub) | |
|--|----------|
| USE | CLIMATE |
| Normal | Moderate |
| PRODUCT RECOMMENDATION 1 | |
| Agrifluid HT-Plus | |
| Check every 250 hours, change every 100 | 00 hours |
| USE | CLIMATE |
| Initial service | Moderate |
| PRODUCT RECOMMENDATION 1 | |
| Agrifluid HT-Plus | |
| Change every 50 hours | |

The data mentioned in this product information sheet is meant to enable the reader to orientate himself about the properties and possible applications of our products. Although this overview is composed with all possible care on the stated date, the compiler does not accept any liability for damages caused by incompleteness and/or inaccuracies in this information, especially when these are caused by obvious typing errors. The terms of delivery of the supplier apply to all product supplies. The reader is advised, especially for critical applications, to make the final product choice in consultation with the supplier. Due to continual product research and development, the information contained herein is subject to changes without notification.