JLG TELEHANDLERS 534D9 CUMMINS QSB4.5 (0160000447 ->)



ENGINE Cummins QSB4.5 Capacity: 10,4 liter, Filter capacity: 0,9 li	ter		
USE		CLIMATE	
Normal		Moderate	
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2		
Dieselfleet CD+ 15W-40	Multifleet SHPD 15W-40		
Check every 10 hours, change every 250 hours			
USE		CLIMATE	
Initial service		Moderate	
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2		
Dieselfleet CD+ 15W-40	Multifleet SHPD 15W-40		
Change every 50 hours			

DIFFERENTIAL FRONT Capacity: 18,5 liter			
USE		CLIMATE	
Normal		Moderate	
PRODUCT RECOMMENDATION 1			
Agrifluid HT-Plus			
Check every 250 hours, change every 1000 hours			
USE		CLIMATE	
Initial service		Moderate	
PRODUCT RECOMMENDATION 1			
Agrifluid HT-Plus			
Change every 50 hours			

HYDRAULIC SYSTEM Capacity: 113,5 liter (Reservoir), Capacity: 178 liter (System)				
USE		CLIMATE		
Normal		Moderate		
PRODUCT RECOMMENDATION 1				
Agrifluid HT-Plus				
Check every 10 hours, change every 1500 hours				

JLG TELEHANDLERS 534D9 CUMMINS QSB4.5 (0160000447 ->)



COOLING SYSTEM Capacity: 20,8 liter			
USE		CLIMATE	
Normal		Moderate	
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2		
Coolant -38 Organic NF	Coolant -26		
Check every 50 hours, change every 1500 hours			

WHEEL DRIVE HUB Capacity: 1,4 liter (each hub)		
USE		CLIMATE
Normal		Moderate
PRODUCT RECOMMENDATION 1		
Agrifluid HT-Plus		
Check every 250 hours, change every 1000 hours		
USE		CLIMATE
Initial service		Moderate
PRODUCT RECOMMENDATION 1		
Agrifluid HT-Plus		
Change every 50 hours		

The data mentioned in this product information sheet is meant to enable the reader to orientate himself about the properties and possible applications of our products. Although this overview is composed with all possible care on the stated date, the compiler does not accept any liability for damages caused by incompleteness and/or inaccuracies in this information, especially when these are caused by obvious typing errors. The terms of delivery of the supplier apply to all product supplies. The reader is advised, especially for critical applications, to make the final product choice in consultation with the supplier. Due to continual product research and development, the information contained herein is subject to changes without notification.