

# JLG TELEHANDLERS G6-23A DEUTZ BF4M-2012

**ENGINE** Deutz BF4M-2012

Capacity: 9 liter, Filter capacity: 1 liter

| USE    | CLIMATE  |
|--------|----------|
| Normal | Moderate |

## PRODUCT RECOMMENDATION 1

**Dieselfleet CD+ 15W-40**

## PRODUCT RECOMMENDATION 2

**Multifleet SHPD 15W-40***Check every 10 hours, change every 250 hours*

| USE             | CLIMATE  |
|-----------------|----------|
| Initial service | Moderate |

## PRODUCT RECOMMENDATION 1

**Dieselfleet CD+ 15W-40**

## PRODUCT RECOMMENDATION 2

**Multifleet SHPD 15W-40***Change every 50 hours***DIFFERENTIAL FRONT**

Capacity: 8 liter

| USE    | CLIMATE  |
|--------|----------|
| Normal | Moderate |

## PRODUCT RECOMMENDATION 1

**Gearlube LS 80W-90***Check every 250 hours, change every 1000 hours*

| USE             | CLIMATE  |
|-----------------|----------|
| Initial service | Moderate |

## PRODUCT RECOMMENDATION 1

**Gearlube LS 80W-90***Change every 50 hours***DIFFERENTIAL REAR**

Capacity: 7,8 liter

| USE    | CLIMATE  |
|--------|----------|
| Normal | Moderate |

## PRODUCT RECOMMENDATION 1

**Gearlube LS 80W-90***Check every 250 hours, change every 1000 hours*

| USE             | CLIMATE  |
|-----------------|----------|
| Initial service | Moderate |

## PRODUCT RECOMMENDATION 1

**Gearlube LS 80W-90***Change every 50 hours*

# JLG TELEHANDLERS G6-23A DEUTZ BF4M-2012



## HUB REDUCTIONS FRONT

Capacity: 0,65 liter (each hub)

| USE    | CLIMATE  |
|--------|----------|
| Normal | Moderate |

PRODUCT RECOMMENDATION 1

**Gearlube LS 80W-90***Check every 250 hours, change every 1000 hours*

| USE             | CLIMATE  |
|-----------------|----------|
| Initial service | Moderate |

PRODUCT RECOMMENDATION 1

**Gearlube LS 80W-90***Change every 50 hours*

## HUB REDUCTIONS REAR

Capacity: 0,65 liter (each hub)

| USE    | CLIMATE  |
|--------|----------|
| Normal | Moderate |

PRODUCT RECOMMENDATION 1

**Gearlube LS 80W-90***Check every 250 hours, change every 1000 hours*

| USE             | CLIMATE  |
|-----------------|----------|
| Initial service | Moderate |

PRODUCT RECOMMENDATION 1

**Gearlube LS 80W-90***Change every 50 hours*

## HYDRAULIC SYSTEM

Capacity: 87 liter (Reservoir), Capacity: 133 liter (System)

| USE    | CLIMATE  |
|--------|----------|
| Normal | Moderate |

PRODUCT RECOMMENDATION 1

**Agrifluid Synth XHP Ultra**

PRODUCT RECOMMENDATION 2

**Agrifluid HT-Plus**

PRODUCT RECOMMENDATION 3

**Kroontrak MTH 10W-30***Check every 8 hours, change every 1500 hours*

# JLG TELEHANDLERS G6-23A DEUTZ BF4M-2012



## HYDRAULIC BRAKE SYSTEM

Capacity: 0,7 liter

| USE    | CLIMATE  |
|--------|----------|
| Normal | Moderate |

PRODUCT RECOMMENDATION 1

**ATF Dexron II-D**

Check every 8 hours, change every 1500 hours

## COOLING SYSTEM

Capacity: 15,1 liter

| USE    | CLIMATE  |
|--------|----------|
| Normal | Moderate |

PRODUCT RECOMMENDATION 1

**Coolant -38 Organic NF**

PRODUCT RECOMMENDATION 2

**Coolant -26**

Check every 50 hours, change every 1500 hours

The data mentioned in this product information sheet is meant to enable the reader to orientate himself about the properties and possible applications of our products. Although this overview is composed with all possible care on the stated date, the compiler does not accept any liability for damages caused by incompleteness and/or inaccuracies in this information, especially when these are caused by obvious typing errors. The terms of delivery of the supplier apply to all product supplies. The reader is advised, especially for critical applications, to make the final product choice in consultation with the supplier. Due to continual product research and development, the information contained herein is subject to changes without notification.