JLG TELEHANDLERS L2906H DEUTZ TCD2012 L04 2V T3/IIIA



ENGINE Deutz TCD 2012 L04 2V Capacity: 10,4 liter, Filter capacity: 1	liter	
USE		CLIMATE
Initial service		Mediterranean
PRODUCT RECOMMENDATION 1		
Multifleet SHPD 20W-50		
Change every 50 hours		
USE		CLIMATE
Initial service		Moderate
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	PRODUCT RECOMMENDATION 3
Kroontrak CVT 10W-40	Agrisynth MSP 10W-40	Agridiesel MSP 15W-40
Change every 50 hours		
USE		CLIMATE
Normal, fuel sulfur level <0,5 %	, ambient temperature > -10°C	Mediterranean
PRODUCT RECOMMENDATION 1		
Multifleet SHPD 20W-50		
Check every 10 hours, change every	/ 250 hours	
USE		CLIMATE
Normal, fuel sulfur level <0,5 %	, ambient temperature > -10°C	Moderate
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	PRODUCT RECOMMENDATION 3
Kroontrak CVT 10W-40	Agrisynth MSP 10W-40	Agridiesel MSP 15W-40
Check every 10 hours, change every	, 250 hours	

Capacity: 9,5 liter		
USE		CLIMATE
Normal		Moderate
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	PRODUCT RECOMMENDATION 3
Agrifluid Synth XHP Ultra	Agrifluid HT-Plus	Kroontrak MTH 10W-30
Check every 250 hours, change every	/ 1500 hours	·
USE		CLIMATE
Initial service		Moderate
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	PRODUCT RECOMMENDATION 3
Agrifluid Synth XHP Ultra	Agrifluid HT-Plus	Kroontrak MTH 10W-30
01 1501		

Change every 150 hours

JLG TELEHANDLERS L2906H DEUTZ TCD2012 L04 2V T3/IIIA



Agrifluid Synth XHP Ultra	Agrifluid HT-Plus	Kroontrak MTH 10W-30
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	PRODUCT RECOMMENDATION 3
Initial service		Moderate
USE		CLIMATE
Check every 250 hours, change every 15	00 hours	
Agrifluid Synth XHP Ultra	Agrifluid HT-Plus	Kroontrak MTH 10W-30
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	PRODUCT RECOMMENDATION 3
Normal		Moderate
USE		CLIMATE
DIFFERENTIAL REAR Capacity: 5,5 liter		

Change every 150 hours

TRANSFERBOX Capacity: 0,5 liter		
USE		CLIMATE
Normal		Moderate
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	PRODUCT RECOMMENDATION 3
Agrifluid Synth XHP Ultra	Agrifluid HT-Plus	Kroontrak MTH 10W-30
Check every 250 hours, change every 1	500 hours	
USE		CLIMATE
Initial service		Moderate
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	PRODUCT RECOMMENDATION 3
Agrifluid Synth XHP Ultra	Agrifluid HT-Plus	Kroontrak MTH 10W-30

Change every 150 hours

HYDRAULIC SYSTEM Capacity: 60 liter (Reservoir), Capacity: 9	98 liter (System)	
USE		CLIMATE
Normal		Moderate
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	PRODUCT RECOMMENDATION 3
Agrifluid Synth XHP Ultra	Agrifluid HT-Plus	Kroontrak MTH 10W-30

Check every 10 hours, change every 1500 hours

JLG TELEHANDLERS L2906H DEUTZ TCD2012 L04 2V T3/IIIA



COOLING SYSTEM Capacity: 19 liter, Capacity: 3 liter (Reserv	oir)		
USE		CLIMATE	
Normal		Moderate	
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2		
Coolant -38 Organic NF	Coolant -26		

Check every 50 hours, change every 1500 hours

WHEEL DRIVE HUB Capacity: 0,8 liter (each hub)		
USE		CLIMATE
Normal		Moderate
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	PRODUCT RECOMMENDATION 3
Agrifluid Synth XHP Ultra	Agrifluid HT-Plus	Kroontrak MTH 10W-30
Check every 250 hours, change every	y 1500 hours	
USE		CLIMATE

Initial service		Moderate
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	PRODUCT RECOMMENDATION 3
Agrifluid Synth XHP Ultra	Agrifluid HT-Plus	Kroontrak MTH 10W-30
Change every 150 hours		

The data mentioned in this product information sheet is meant to enable the reader to orientate himself about the properties and possible applications of our products. Although this overview is composed with all possible care on the stated date, the compiler does not accept any liability for damages caused by incompleteness and/or inaccuracies in this information, especially when these are caused by obvious typing errors. The terms of delivery of the supplier apply to all product supplies. The reader is advised, especially for critical applications, to make the final product choice in consultation with the supplier. Due to continual product research and development, the information contained herein is subject to changes without notification.