

JLG VERTICAL MAST LIFTS 36EL**HYDRAULIC SYSTEM**

Capacity: 4,7 liter

USE		CLIMATE
Normal		Moderate
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	PRODUCT RECOMMENDATION 3
Agrifluid Synth XHP Ultra	Agrifluid HT-Plus	Kroontrak MTH 10W-30

*Change every 1200 hours/ 24 months***LEVELING JACK SCREWS**

USE		CLIMATE
Normal		Moderate
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	PRODUCT RECOMMENDATION 3
Labora Grease	Q5 MP Calcep Grease EP 2	MP Lithep Grease EP 2

*Change every 6 months/ 300 hours***MAST CHAINS**

USE		CLIMATE
Normal		Moderate
PRODUCT RECOMMENDATION 1		
Industrial Chain Spray		

*Change every 6 months/ 300 hours***SWIVEL RACEWAYS**

USE		CLIMATE
Normal		Moderate
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	PRODUCT RECOMMENDATION 3
Labora Grease	Q5 MP Calcep Grease EP 2	MP Lithep Grease EP 2

Change every 6 months/ 300 hours

The data mentioned in this product information sheet is meant to enable the reader to orientate himself about the properties and possible applications of our products. Although this overview is composed with all possible care on the stated date, the compiler does not accept any liability for damages caused by incompleteness and/or inaccuracies in this information, especially when these are caused by obvious typing errors. The terms of delivery of the supplier apply to all product supplies. The reader is advised, especially for critical applications, to make the final product choice in consultation with the supplier. Due to continual product research and development, the information contained herein is subject to changes without notification.