JOHN DEERE CONSTRUCTION TRACKED EXCAVATORS 135D (2008 AND AFTER)



ENGINE Isuzu 4JJ1X Capacity: 17 liter		
USE		CLIMATE
Normal		Moderate
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	PRODUCT RECOMMENDATION 3
Agrisynth LSP Ultra FE 5W-30	Agrisynth MSP 10W-40	Agridiesel MSP 15W-40

Check every 10 hours, change every 500 hours

Check every 10 hours, change every 5000 hours

HYDRAULIC SYSTEM Capacity: 66 liter (Hydraulic tank), Capacity: 120 liter (System)			
USE		CLIMATE	
Preferred, extended		Moderate	
PRODUCT RECOMMENDATION 1			
Perlus H 46			
Check every 10 hours, change every 5000 hours			
USE		CLIMATE	
Normal		Moderate	
PRODUCT RECOMMENDATION 1			
Perlus H 46			
Check every 10 hours, change every 5000 hours			
USE		CLIMATE	
Normal		Cold	
PRODUCT RECOMMENDATION 1			
Perlus H 32			

COOLING SYSTEM Capacity: 16 liter		
USE		CLIMATE
Normal		Moderate
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	
Coolant -38 Organic NF	Coolant -26	
Check every 10 hours, change every 6000 hours		

JOHN DEERE CONSTRUCTION TRACKED EXCAVATORS 135D (2008 AND AFTER)



SWING REDUCTION UNIT Capacity: 3,2 liter		
USE		CLIMATE
Normal		Moderate
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	
Gearlube GL-5 80W-90	Unigear HS GL-3/GL-5 80W-90	
Charles war 250 hours above a vary 4000 hours		

Check every 250 hours, change every 1000 hours

TRAVEL REDUCTION UNIT Capacity: 4,2 liter (each)		
USE		CLIMATE
Normal		Moderate
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	
Gearlube GL-5 80W-90	Unigear HS GL-3/GL-5 80W-90	

Check every 250 hours, change every 2000 hours

The data mentioned in this product information sheet is meant to enable the reader to orientate himself about the properties and possible applications of our products. Although this overview is composed with all possible care on the stated date, the compiler does not accept any liability for damages caused by incompleteness and/or inaccuracies in this information, especially when these are caused by obvious typing errors. The terms of delivery of the supplier apply to all product supplies. The reader is advised, especially for critical applications, to make the final product choice in consultation with the supplier. Due to continual product research and development, the information contained herein is subject to changes without notification.