

JUNGHEINRICH FORKLIFT TRUCKS, DIESEL DFG DFG 50 CK CX-J PERKINS 1004.42 (2001-2003)



ENGINE Perkins 1004-42
Capacity: 6,9 liter

| USE | CLIMATE |
|--------|----------|
| Normal | Tropical |

| PRODUCT RECOMMENDATION 1 | PRODUCT RECOMMENDATION 2 | PRODUCT RECOMMENDATION 3 |
|------------------------------|-------------------------------|-------------------------------|
| Agridiesel MSP 15W-40 | Agridiesel CRD+ 15W-40 | Dieselfleet CD+ 15W-40 |

Check every 50 hours, change every 3 months/ 500 hours

| USE | CLIMATE |
|--------|---------------|
| Normal | Mediterranean |

| PRODUCT RECOMMENDATION 1 | PRODUCT RECOMMENDATION 2 | PRODUCT RECOMMENDATION 3 |
|-----------------------------|-----------------------------|---------------------------|
| Kroontrak MTH 10W-30 | Synfleet SHPD 10W-40 | Armado Synth 5W-30 |

Check every 50 hours, change every 3 months/ 500 hours

DIFFERENTIAL

Capacity: 3,5 liter (Single drive wheels), Capacity: 4,5 liter (Twin drive wheels)

| USE | CLIMATE |
|--------|----------|
| Normal | Tropical |

| PRODUCT RECOMMENDATION 1 | | |
|------------------------------|--|--|
| Gearlube GL-5 85W-140 | | |

Check every 3 months/ 500 hours, change every 12 months/ 2000 hours

| USE | CLIMATE |
|--------|---------------|
| Normal | Mediterranean |

| PRODUCT RECOMMENDATION 1 | PRODUCT RECOMMENDATION 2 | |
|-----------------------------|------------------------------------|--|
| Gearlube GL-5 80W-90 | Unigear HS GL-3/GL-5 80W-90 | |

Check every 3 months/ 500 hours, change every 12 months/ 2000 hours

| USE | CLIMATE |
|--------|---------|
| Normal | Cold |

| PRODUCT RECOMMENDATION 1 | PRODUCT RECOMMENDATION 2 | |
|--------------------------|--------------------------|--|
| SP Gear 5015 | SP Gear 1071 | |

Check every 3 months/ 500 hours, change every 12 months/ 2000 hours

TRANSMISSION

Capacity: 12,5 liter

| USE | CLIMATE |
|--------|----------|
| Normal | Moderate |

| PRODUCT RECOMMENDATION 1 | | |
|------------------------------|--|--|
| Multifleet SCD 20W-20 | | |

Check every 3 months/ 500 hours, change every 12 months/ 2000 hours

JUNGHEINRICH FORKLIFT TRUCKS, DIESEL DFG DFG 50 CK CX-J PERKINS 1004.42 (2001-2003)

**HYDRAULIC SYSTEM**

Capacity: 70 liter (Hydraulic tank), Capacity: 80 liter (System)

| USE | | CLIMATE |
|--------------------------|--------------------------|----------|
| Normal | | Tropical |
| PRODUCT RECOMMENDATION 1 | PRODUCT RECOMMENDATION 2 | |
| HDX 20W-20 | Perlus H 68 | |

Check every 3 months/ 500 hours, change every 12 months/ 2000 hours

| USE | | CLIMATE |
|--------------------------|--------------------------|----------|
| Normal | | Moderate |
| PRODUCT RECOMMENDATION 1 | PRODUCT RECOMMENDATION 2 | |
| HDX 10W | Perlus H 46 | |

*Check every 3 months/ 500 hours, change every 12 months/ 2000 hours***HYDRAULIC BRAKE SYSTEM**

Capacity: 0,29 liter

| USE | | CLIMATE |
|----------------------------------|---------------------------|--------------------------|
| Normal | | Moderate |
| PRODUCT RECOMMENDATION 1 | PRODUCT RECOMMENDATION 2 | PRODUCT RECOMMENDATION 3 |
| Drauliquid-LV Super DOT 4 | Drauliquid-S DOT 4 | Drauliquid DOT 3 |

*Check every 3 months/ 500 hours, change every 12 months/ 2000 hours***GREASE POINTS/NIPPLES**

| USE | | CLIMATE |
|--------------------------|---------------------------------|------------------------------|
| Normal | | Moderate |
| PRODUCT RECOMMENDATION 1 | PRODUCT RECOMMENDATION 2 | PRODUCT RECOMMENDATION 3 |
| Labora Grease | Q5 MP Calcep Grease EP 2 | MP Lithep Grease EP 2 |

COOLING SYSTEM

Capacity: 16 liter

| USE | | CLIMATE |
|--------------------------|--------------------------|-------------------------------|
| Normal | | Moderate |
| PRODUCT RECOMMENDATION 1 | PRODUCT RECOMMENDATION 2 | PRODUCT RECOMMENDATION 3 |
| Coolant SP 15+ | Coolant SP 12 | Coolant -38 Organic NF |

Check every 50 hours, change every 1000 hours/ 12 months

JUNGHEINRICH FORKLIFT TRUCKS, DIESEL DFG DFG 50 CK CX-J PERKINS 1004.42 (2001-2003)

**REDUCTION UNIT**

Capacity: 1 liter

| USE | CLIMATE |
|--------|----------|
| Normal | Tropical |

PRODUCT RECOMMENDATION 1

Gearlube GL-5 85W-140*Check every 3 months/ 500 hours, change every 12 months/ 2000 hours*

| USE | CLIMATE |
|--------|---------------|
| Normal | Mediterranean |

PRODUCT RECOMMENDATION 1

Gearlube GL-5 80W-90

PRODUCT RECOMMENDATION 2

Unigear HS GL-3/GL-5 80W-90*Check every 3 months/ 500 hours, change every 12 months/ 2000 hours*

| USE | CLIMATE |
|--------|---------|
| Normal | Cold |

PRODUCT RECOMMENDATION 1

SP Gear 5015

PRODUCT RECOMMENDATION 2

SP Gear 1071*Check every 3 months/ 500 hours, change every 12 months/ 2000 hours*

The data mentioned in this product information sheet is meant to enable the reader to orientate himself about the properties and possible applications of our products. Although this overview is composed with all possible care on the stated date, the compiler does not accept any liability for damages caused by incompleteness and/or inaccuracies in this information, especially when these are caused by obvious typing errors. The terms of delivery of the supplier apply to all product supplies. The reader is advised, especially for critical applications, to make the final product choice in consultation with the supplier. Due to continual product research and development, the information contained herein is subject to changes without notification.