JUNGHEINRICH FORKLIFT TRUCKS, DIESEL DFG DFG 50 CK CX-J PERKINS 1104C-44 (2001-2004)



ENGINE Perkins 1104C-44 Capacity: 6,9 liter		
USE		CLIMATE
Normal		Tropical
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	PRODUCT RECOMMENDATION 3
Agridiesel MSP 15W-40	Agridiesel CRD+ 15W-40	Dieselfleet CD+ 15W-40
Check every 50 hours, change every 3 mo	onths/ 500 hours	
USE		CLIMATE
Normal		Mediterranean
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	PRODUCT RECOMMENDATION 3

Synfleet SHPD 10W-40	Armado Synth 5W-30	Dieselfleet LSP Ultra 10W-30

Check every 50 hours, change every 3 months/ 500 hours

DIFFERENTIAL Capacity: 3,5 liter (Single drive wheels), Capacity: 4,5 liter (Twin drive wheels)		
USE	CLIMATE	
Normal	Tropical	
PRODUCT RECOMMENDATION 1		
Gearlube GL-5 85W-140		
	· · · · · · · · · · · · · · · · · · ·	

Check every 3 months/ 500 hours, change every 12 months/ 2000 hours

USE		CLIMATE
Normal		Mediterranean
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	
Gearlube GL-5 80W-90	Unigear HS GL-3/GL-5 80W-90	

Check every 3 months/ 500 hours, change every 12 months/ 2000 hours

USE		CLIMATE
Normal		Cold
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	
SP Gear 5015	SP Gear 1071	

Check every 3 months/ 500 hours, change every 12 months/ 2000 hours

TRANSMISSION Capacity: 12,5 liter		
USE		CLIMATE
Normal		Moderate
PRODUCT RECOMMENDATION 1		
Multifleet SCD 20W-20		
Check every 3 months/ 500 hours change	even 12 months/2000 hours	

Check every 3 months/ 500 hours, change every 12 months/ 2000 hours

JUNGHEINRICH FORKLIFT TRUCKS, DIESEL DFG DFG 50 CK CX-J PERKINS 1104C-44 (2001-2004)



HYDRAULIC SYSTEM

Capacity: 70 liter (Hydraulic tank), Capacity: 80 liter (System)		
USE		CLIMATE
Normal		Tropical
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	
HDX 20W-20	Perlus H 68	
Check every 3 months/ 500 hours, change every 12 months/ 2000 hours		
USE		CLIMATE
Normal		Moderate

PRODUCT RECOMMENDATION 2

Perlus H 46

PRODUCT RECOMMENDATION 1
HDX 10W

Check every 3 months/ 500 hours, change every 12 months/ 2000 hours

HYDRAULIC BRAKE SYSTEM Capacity: 0,29 liter		
USE		CLIMATE
Normal		Moderate
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	PRODUCT RECOMMENDATION 3
Drauliquid-LV Super DOT 4	Drauliquid-S DOT 4	Drauliquid DOT 3

Check every 3 months/ 500 hours, change every 12 months/ 2000 hours

GREASE POINTS/NIPPLES		
USE		CLIMATE
Normal		Moderate
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	PRODUCT RECOMMENDATION 3
Labora Grease	Q5 MP Calcep Grease EP 2	MP Lithep Grease EP 2

	CLIMATE
	Moderate
PRODUCT RECOMMENDATION 2	PRODUCT RECOMMENDATION 3
Coolant SP 12	Coolant -38 Organic NF

Check every 50 hours, change every 1000 hours/ 12 months

JUNGHEINRICH FORKLIFT TRUCKS, DIESEL DFG DFG 50 CK CX-J PERKINS 1104C-44 (2001-2004)



REDUCTION UNIT Capacity: 1 liter		
USE		CLIMATE
Normal		Tropical
PRODUCT RECOMMENDATION 1		
Gearlube GL-5 85W-140		
Check every 3 months/ 500 hours, change	every 12 months/ 2000 hours	
USE		CLIMATE
Normal		Mediterranean
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	
Gearlube GL-5 80W-90	Unigear HS GL-3/GL-5 80W-90	
Check every 3 months/ 500 hours, change	every 12 months/ 2000 hours	

USE		CLIMATE
Normal		Cold
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	
SP Gear 5015	SP Gear 1071	
Check every 3 months/ 500 hours, change every 12 months/ 2000 hours		

The data mentioned in this product information sheet is meant to enable the reader to orientate himself about the properties and possible applications of our products. Although this overview is composed with all possible care on the stated date, the compiler does not accept any liability for damages caused by incompleteness and/or inaccuracies in this information, especially when these are caused by obvious typing errors. The terms of delivery of the supplier apply to all product supplies. The reader is advised, especially for critical applications, to make the final product choice in consultation with the supplier. Due to continual product research and development, the information contained herein is subject to changes without notification.