JUNGHEINRICH FORKLIFT TRUCKS, LPG TFG TFG 20 AK AX-J MAZDA FE (2001-2003)



Capacity: 4,3 liter		
USE		CLIMATE
Normal		Mediterranean
PRODUCT RECOMMENDATION 1		
Kroontrak MTH 10W-30		
Check every 50 hours, change every 3 mg	onths/ 500 hours	
USE		CLIMATE
Normal		Cold
PRODUCT RECOMMENDATION 1		
HDX 10W		
Check every 50 hours, change every 3 mc	onths/ 500 hours	
DIFFERENTIAL Capacity: 5 liter		
USE		CLIMATE
Normal		Tropical
PRODUCT RECOMMENDATION 1		
Gearlube GL-5 85W-140		
Check every 3 months/ 500 hours, change	e every 12 months/ 2000 hours	
USE		CLIMATE
Normal		Mediterranean
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	
Gearlube GL-5 80W-90	Unigear HS GL-3/GL-5 80W-90	

USE		CLIMATE
Normal		Cold
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	

PRODUCT RECOMMENDATION 1 PRODUCT RECOMMENDATION 2

SP Gear 5015 SP Gear 1071

Check every 3 months/ 500 hours, change every 12 months/ 2000 hours

Check every 3 months/500 hours, change every 12 months/2000 hours

TRANSMISSION Capacity: 7 liter	
USE	CLIMATE
Normal	Moderate
PRODUCT RECOMMENDATION 1	
Multifleet SCD 20W-20	
Check every 3 months/ 500 hours, change ever	ery 12 months/ 2000 hours

JUNGHEINRICH FORKLIFT TRUCKS, LPG TFG TFG 20 AK AX-J MAZDA FE (2001-2003)



HYDRAULIC SYSTEM Capacity: 46 liter (Hydraulic tank), Capacity: 51 liter (System)		
USE		CLIMATE
Normal		Tropical
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	
HDX 20W-20	Perlus H 68	
Check every 3 months/ 500 hours, change every 12 months/ 2000 hours		
USE		CLIMATE
Normal		Moderate
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	
HDX 10W	Perlus H 46	
Check every 3 months/ 500 hours, change	e every 12 months/ 2000 hours	

HYDRAULIC BRAKE SYSTEM Capacity: 0,45 liter		
USE		CLIMATE
Normal		Moderate
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	PRODUCT RECOMMENDATION 3
Drauliquid-LV Super DOT 4	Drauliquid-S DOT 4	Drauliquid DOT 3
Check every 3 months/ 500 hours, cha	nae every 12 months/ 2000 hours	'

GREASE POINTS/NIPPLES		
USE		CLIMATE
Normal		Moderate
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	PRODUCT RECOMMENDATION 3
Labora Grease	Q5 MP Calcep Grease EP 2	MP Lithep Grease EP 2

COOLING SYSTEM Capacity: 9 liter		
USE		CLIMATE
Normal		Moderate
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	PRODUCT RECOMMENDATION 3
Coolant SP 15+	Coolant SP 12	Coolant -38 Organic NF
Check every 50 hours, change eve	ry 1000 hours/ 12 months	'

The data mentioned in this product information sheet is meant to enable the reader to orientate himself about the properties and possible applications of our products. Although this overview is composed with all possible care on the stated date, the compiler does not accept any liability for damages caused by incompleteness and/or inaccuracies in this information, especially when these are caused by obvious typing errors. The terms of delivery of the supplier apply to all product supplies. The reader is advised, especially for critical applications, to make the final product choice in consultation with the supplier. Due to continual product research and development, the information contained herein is subject to changes without notification.