

# JUNGHEINRICH FORKLIFT TRUCKS, LPG

## TFG TFG 45 CS CH-J GM 4.3L V6 (2001-2004)



**ENGINE** GM 4.3L V6  
Capacity: 4,7 liter

| USE    | CLIMATE  |
|--------|----------|
| Normal | Tropical |

PRODUCT RECOMMENDATION 1

**Multifleet SCD 40**

*Check every 50 hours, change every 3 months/ 500 hours*

| USE    | CLIMATE       |
|--------|---------------|
| Normal | Mediterranean |

PRODUCT RECOMMENDATION 1

**Dieselfleet CD+ 15W-40**

PRODUCT RECOMMENDATION 2

**Multifleet SHPD 15W-40**

*Check every 50 hours, change every 3 months/ 500 hours*

| USE    | CLIMATE |
|--------|---------|
| Normal | Cold    |

PRODUCT RECOMMENDATION 1

**Asyntho 5W-30**

PRODUCT RECOMMENDATION 2

**Synfleet SHPD 10W-40**

*Check every 50 hours, change every 3 months/ 500 hours*

**HYDRAULIC SYSTEM**

Capacity: 70 liter (Hydraulic tank), Capacity: 80 liter (System)

| USE    | CLIMATE  |
|--------|----------|
| Normal | Tropical |

PRODUCT RECOMMENDATION 1

**HDX 20W-20**

PRODUCT RECOMMENDATION 2

**Perlus H 68**

*Check every 3 months/ 500 hours, change every 12 months/ 2000 hours*

| USE    | CLIMATE  |
|--------|----------|
| Normal | Moderate |

PRODUCT RECOMMENDATION 1

**HDX 10W**

PRODUCT RECOMMENDATION 2

**Perlus H 46**

*Check every 3 months/ 500 hours, change every 12 months/ 2000 hours*

**GREASE POINTS/NIPPLES**

| USE    | CLIMATE  |
|--------|----------|
| Normal | Moderate |

PRODUCT RECOMMENDATION 1

**Labora Grease**

PRODUCT RECOMMENDATION 2

**Q5 MP Calcep Grease EP 2**

PRODUCT RECOMMENDATION 3

**MP Lithep Grease EP 2**

# JUNGHEINRICH FORKLIFT TRUCKS, LPG

## TFG TFG 45 CS CH-J GM 4.3L V6 (2001-2004)

**COOLING SYSTEM**

Capacity: 7,3 liter

| USE                      |                          | CLIMATE                       |
|--------------------------|--------------------------|-------------------------------|
| Normal                   |                          | Moderate                      |
| PRODUCT RECOMMENDATION 1 | PRODUCT RECOMMENDATION 2 | PRODUCT RECOMMENDATION 3      |
| <b>Coolant SP 15+</b>    | <b>Coolant SP 12</b>     | <b>Coolant -38 Organic NF</b> |

*Check every 50 hours, change every 1000 hours/ 12 months*

*The data mentioned in this product information sheet is meant to enable the reader to orientate himself about the properties and possible applications of our products. Although this overview is composed with all possible care on the stated date, the compiler does not accept any liability for damages caused by incompleteness and/or inaccuracies in this information, especially when these are caused by obvious typing errors. The terms of delivery of the supplier apply to all product supplies. The reader is advised, especially for critical applications, to make the final product choice in consultation with the supplier. Due to continual product research and development, the information contained herein is subject to changes without notification.*