

# KALMAR FORKLIFT TRUCKS, DIESEL DC 10-600 XL 10T

**ENGINE** Perkins 1006.6

USE	CLIMATE
Normal	Moderate

PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	
<b>Dieselfleet CD+ 15W-40</b>	<b>Multifleet SHPD 15W-40</b>	

*Change every 200 hours*

USE	CLIMATE
Initial service	Moderate

PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	
<b>Dieselfleet CD+ 15W-40</b>	<b>Multifleet SHPD 15W-40</b>	

*Change every 50 hours*

**DIFFERENTIAL DRIVE AXLE**

USE	CLIMATE
Normal	Moderate

PRODUCT RECOMMENDATION 1		
<b>Gearlube HS GL-5 80W-140</b>		

*Change every 6 months/ 1200 hours*

**HUB REDUCTIONS DRIVE AXLE**

USE	CLIMATE
Normal	Moderate

PRODUCT RECOMMENDATION 1		
<b>Gearlube HS GL-5 80W-140</b>		

*Change every 6 months/ 1200 hours*

**TRANSMISSION**

USE	CLIMATE
Normal	Mediterranean

PRODUCT RECOMMENDATION 1		
<b>Gear Oil Alcat 30</b>		

*Change every 6 months/ 1200 hours*

USE	CLIMATE
Normal	Moderate

PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	
<b>Gear Oil Alcat 10W</b>	<b>ATF Dexron II-D</b>	

*Change every 6 months/ 1200 hours*

# KALMAR FORKLIFT TRUCKS, DIESEL DC 10-600 XL 10T



## HYDRAULIC SYSTEM

USE		CLIMATE
Normal		Moderate
PRODUCT RECOMMENDATION 1		
<b>Perlus H 32</b>		
<i>Change every 6 months/ 1200 hours</i>		

## GREASE POINTS/NIPPLES

USE		CLIMATE
Normal		Moderate
PRODUCT RECOMMENDATION 1		
<b>MoS2 Grease EP 2</b>		

## WHEEL BEARINGS

USE		CLIMATE
Normal		Moderate
PRODUCT RECOMMENDATION 1		
<b>MoS2 Grease EP 2</b>		

*The data mentioned in this product information sheet is meant to enable the reader to orientate himself about the properties and possible applications of our products. Although this overview is composed with all possible care on the stated date, the compiler does not accept any liability for damages caused by incompleteness and/or inaccuracies in this information, especially when these are caused by obvious typing errors. The terms of delivery of the supplier apply to all product supplies. The reader is advised, especially for critical applications, to make the final product choice in consultation with the supplier. Due to continual product research and development, the information contained herein is subject to changes without notification.*