KALMAR FORKLIFT TRUCKS, DIESEL DC 5-600 5T



ENGINE Perkins 1006.6			
USE		CLIMATE	
Normal		Moderate	
PRODUCT RECOMMENDATION 1 PRODUCT RECOMMENDATION 2			
Dieselfleet CD+ 15W-40	Multifleet SHPD 15W-40		
Change every 200 hours			
USE		CLIMATE	
Initial service		Moderate	
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2		
Dieselfleet CD+ 15W-40	Multifleet SHPD 15W-40		
Change every 50 hours	·		

DIFFERENTIAL DRIVE AXLE	
USE	CLIMATE
Normal	Moderate
PRODUCT RECOMMENDATION 1	
Gearlube HS GL-5 80W-140	
Change every 6 months/ 1200 hours	·

HUB REDUCTIONS DRIVE AXLE	
USE	CLIMATE
Normal	Moderate
PRODUCT RECOMMENDATION 1	
Gearlube HS GL-5 80W-140	
Change every 6 months/ 1200 hours	·

USE	CLIMATE	
Normal	Mediterranean	
PRODUCT RECOMMENDATION 1		
Multifleet SCD 30		
Change every 6 months/ 1200 hours		
USE	CLIMATE	
Normal	Moderate	
PRODUCT RECOMMENDATION 1		
Multifleet SCD 10W		

Change every 6 months/ 1200 hours

KALMAR FORKLIFT TRUCKS, DIESEL DC 5-600 5T



TRANSMISSION Clark	
USE	CLIMATE
Normal	Mediterranean
PRODUCT RECOMMENDATION 1	
Multifleet SCD 30	
Change every 6 months/ 1200 hours	
USE	CLIMATE
Normal	Moderate
PRODUCT RECOMMENDATION 1	
Multifleet SCD 10W	
Change every 6 months/ 1200 hours	
TRANSMISSION Voith	
USE	CLIMATE
Normal	Moderate
PRODUCT RECOMMENDATION 1	
ATF Dexron II-D	
Change every 6 months/ 1200 hours	
HYDRAULIC SYSTEM	
USE	CLIMATE
Normal	Moderate
PRODUCT RECOMMENDATION 1	
Perlus H 32	
Change every 6 months/ 1200 hours	
GREASE POINTS/NIPPLES	
USE	CLIMATE
Normal	Moderate
PRODUCT RECOMMENDATION 1	
MoS2 Grease EP 2	
WHEEL BEARINGS	
USE	CLIMATE
Normal	Moderate
PRODUCT RECOMMENDATION 1	
MoS2 Grease EP 2	

The data mentioned in this product information sheet is meant to enable the reader to orientate himself about the properties and possible applications of our products. Although this overview is composed with all possible care on the stated date, the compiler does not accept any liability for damages caused by incompleteness and/or

PRODUCT RECOMMENDATION

KALMAR FORKLIFT TRUCKS, DIESEL DC 5-600 5T



inaccuracies in this information, especially when these are caused by obvious typing errors. The terms of delivery of the supplier apply to all product supplies. The reader is advised, especially for critical applications, to make the final product choice in consultation with the supplier. Due to continual product research and development, the information contained herein is subject to changes without notification.