

# KALMAR FORKLIFT TRUCKS, ELECTRIC

## EC 6-600 6T



### DIFFERENTIAL DRIVE AXLE

| USE                                      |  | CLIMATE  |
|------------------------------------------|--|----------|
| Normal                                   |  | Moderate |
| PRODUCT RECOMMENDATION 1                 |  |          |
| <b>Gearlube HS GL-5 80W-140</b>          |  |          |
| <i>Change every 6 months/ 1200 hours</i> |  |          |

### HUB REDUCTIONS DRIVE AXLE

| USE                                      |  | CLIMATE  |
|------------------------------------------|--|----------|
| Normal                                   |  | Moderate |
| PRODUCT RECOMMENDATION 1                 |  |          |
| <b>Gearlube HS GL-5 80W-140</b>          |  |          |
| <i>Change every 6 months/ 1200 hours</i> |  |          |

### HYDRAULIC SYSTEM

| USE                                      |  | CLIMATE  |
|------------------------------------------|--|----------|
| Normal                                   |  | Moderate |
| PRODUCT RECOMMENDATION 1                 |  |          |
| <b>Perlus H 32</b>                       |  |          |
| <i>Change every 6 months/ 1200 hours</i> |  |          |

### GREASE POINTS/NIPPLES

| USE                      |  | CLIMATE  |
|--------------------------|--|----------|
| Normal                   |  | Moderate |
| PRODUCT RECOMMENDATION 1 |  |          |
| <b>MoS2 Grease EP 2</b>  |  |          |

### WHEEL BEARINGS

| USE                      |  | CLIMATE  |
|--------------------------|--|----------|
| Normal                   |  | Moderate |
| PRODUCT RECOMMENDATION 1 |  |          |
| <b>MoS2 Grease EP 2</b>  |  |          |

The data mentioned in this product information sheet is meant to enable the reader to orientate himself about the properties and possible applications of our products. Although this overview is composed with all possible care on the stated date, the compiler does not accept any liability for damages caused by incompleteness and/or inaccuracies in this information, especially when these are caused by obvious typing errors. The terms of delivery of the supplier apply to all product supplies. The reader is advised, especially for critical applications, to make the final product choice in consultation with the supplier. Due to continual product research and development, the information contained herein is subject to changes without notification.