

KATO TRACKED EXCAVATORS HD1023 LC

9478101 ->



ENGINE Mitsubishi 6D16-TE1
Capacity: 28 liter

USE	CLIMATE
Normal	Mediterranean

PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2
Agridiesel CRD+ 15W-40	Multifleet SHPD 15W-40

Check every 10 hours, change every 500 hours/ 6 months

USE	CLIMATE
Normal	Moderate

PRODUCT RECOMMENDATION 1	
Kroontrak MTH 10W-30	

Check every 10 hours, change every 500 hours/ 6 months

USE	CLIMATE
Initial service	Mediterranean

PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2
Agridiesel CRD+ 15W-40	Multifleet SHPD 15W-40

Change every 60 hours

USE	CLIMATE
Initial service	Moderate

PRODUCT RECOMMENDATION 1	
Kroontrak MTH 10W-30	

Change every 60 hours

HYDRAULIC SYSTEM

Capacity: 165 liter (Hydraulic tank), Capacity: 310 liter (System)

USE	CLIMATE
Normal	Mediterranean

PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	PRODUCT RECOMMENDATION 3
Perlus H 46	Perlus H 68	Perlus AF 46

Check every 10 hours, change every 2000 hours/ 24 months

USE	CLIMATE
Normal	Moderate

PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	
Perlus H 32	Perlus AF 32	

Check every 10 hours, change every 2000 hours/ 24 months

KATO TRACKED EXCAVATORS HD1023 LC

9478101 ->



GREASE POINTS/NIPPLES

USE		CLIMATE
Normal		Moderate
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	PRODUCT RECOMMENDATION 3
Labora Grease	Q5 MP Calcep Grease EP 2	MP Lithep Grease EP 2

Check every 10 hours, change every 100 hours

COOLING SYSTEM

Capacity: 25,5 liter

USE		CLIMATE
Normal		Moderate
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	
Coolant SP 15+	Coolant SP 12	

Check every 10 hours, change every 24 months

SWING REDUCTION UNIT

Capacity: 11,3 liter (each)

USE		CLIMATE
Normal		Mediterranean
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	
Gearlube GL-5 85W-140	Unigear LS GL-3/GL-5 85W-140	

Check every 250 hours, change every 1000 hours/ 12 months

USE		CLIMATE
Normal		Moderate
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	
Gearlube GL-5 80W-90	Unigear HS GL-3/GL-5 80W-90	

Check every 250 hours, change every 1000 hours/ 12 months

USE		CLIMATE
Initial service		Mediterranean
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	
Gearlube GL-5 85W-140	Unigear LS GL-3/GL-5 85W-140	

Change every 250 hours

USE		CLIMATE
Initial service		Moderate
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	
Gearlube GL-5 80W-90	Unigear HS GL-3/GL-5 80W-90	

Change every 250 hours

KATO TRACKED EXCAVATORS HD1023 LC

9478101 ->



TRACK IDLERS

USE	CLIMATE
Normal	Mediterranean

PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	
Agridiesel CRD+ 15W-40	Multifleet SHPD 15W-40	

Check every 10 hours

USE	CLIMATE
Normal	Moderate

PRODUCT RECOMMENDATION 1		
Kroontrak MTH 10W-30		

Check every 10 hours

TRACK ROLLERS

USE	CLIMATE
Normal	Mediterranean

PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	
Agridiesel CRD+ 15W-40	Multifleet SHPD 15W-40	

Check every 10 hours

USE	CLIMATE
Normal	Moderate

PRODUCT RECOMMENDATION 1		
Kroontrak MTH 10W-30		

Check every 10 hours

KATO TRACKED EXCAVATORS HD1023 LC

9478101 ->

**TRAVEL REDUCTION UNIT**

Capacity: 3,3 liter (each)

USE		CLIMATE
Normal		Mediterranean
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	
Gearlube GL-5 85W-140	Unigear LS GL-3/GL-5 85W-140	

Check every 250 hours, change every 1000 hours/ 12 months

USE		CLIMATE
Normal		Moderate
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	
Gearlube GL-5 80W-90	Unigear HS GL-3/GL-5 80W-90	

Check every 250 hours, change every 1000 hours/ 12 months

USE		CLIMATE
Initial service		Mediterranean
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	
Gearlube GL-5 85W-140	Unigear LS GL-3/GL-5 85W-140	

Check every 250 hours, change every 6 months/ 500 hours

USE		CLIMATE
Initial service		Moderate
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	
Gearlube GL-5 80W-90	Unigear HS GL-3/GL-5 80W-90	

Check every 250 hours, change every 6 months/ 500 hours

The data mentioned in this product information sheet is meant to enable the reader to orientate himself about the properties and possible applications of our products. Although this overview is composed with all possible care on the stated date, the compiler does not accept any liability for damages caused by incompleteness and/or inaccuracies in this information, especially when these are caused by obvious typing errors. The terms of delivery of the supplier apply to all product supplies. The reader is advised, especially for critical applications, to make the final product choice in consultation with the supplier. Due to continual product research and development, the information contained herein is subject to changes without notification.