KAWASAKI WHEELED LOADERS 85 ZV CUMMINS QSL9 TIER 2



ENGINE Cummins QSL9 Capacity: 27 liter		
USE		CLIMATE
Normal		Moderate
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	PRODUCT RECOMMENDATION 3
Agridiesel CRD+ 15W-40	Dieselfleet CD+ 15W-40	Multifleet SHPD 15W-40

Change every 250 hours

DIFFERENTIAL HUB REDUCTIONS FRONT Capacity: 74 liter (each hub)		
USE	CLIMATE	
Normal	Moderate	
PRODUCT RECOMMENDATION 1		
Gear Oil Alcat 50		
Change every 2000 hours	·	

DIFFERENTIAL HUB REDUCTIONS REAR Capacity: 80 liter (each hub)		
USE	CLIMATE	
Normal	Moderate	
PRODUCT RECOMMENDATION 1		
Gear Oil Alcat 50		
Change every 2000 hours	<u>'</u>	

TRANSMISSION Capacity: 38 liter (+ torque converter)	
USE	CLIMATE
Normal	Moderate
PRODUCT RECOMMENDATION 1	
Multifleet SCD 10W	
Change every 1000 hours	

KAWASAKI WHEELED LOADERS 85 ZV CUMMINS QSL9 TIER 2



CLIMATE
Mediterranean
CLIMATE
Arctic

HYDRAULIC BRAKE SYSTEM

We are unable to give a standard recommendation for this component. Please contact our service department.

GREASE POINTS/NIPPLES		
USE		CLIMATE
Normal		Moderate
PRODUCT RECOMMENDATION 1		
MoS2 Grease EP 2		

COOLING SYSTEM Capacity: 58 liter		
USE		CLIMATE
Normal		Moderate
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	
Coolant SP 15+	Coolant SP 12	
Change every 240000 km/ 12 mon	ths/ 4000 hours	'

KAWASAKI WHEELED LOADERS 85 ZV CUMMINS QSL9 TIER 2



	CLIMATE
	Mediterranean
PRODUCT RECOMMENDATION 2	PRODUCT RECOMMENDATION 3
Unigear HS GL-3/GL-5 80W-90	Gearlube GL-5 85W-140
	CLIMATE
	Arctic
PRODUCT RECOMMENDATION 2	
SP Gear 1071	
	Unigear HS GL-3/GL-5 80W-90 PRODUCT RECOMMENDATION 2

The data mentioned in this product information sheet is meant to enable the reader to orientate himself about the properties and possible applications of our products. Although this overview is composed with all possible care on the stated date, the compiler does not accept any liability for damages caused by incompleteness and/or inaccuracies in this information, especially when these are caused by obvious typing errors. The terms of delivery of the supplier apply to all product supplies. The reader is advised, especially for critical applications, to make the final product choice in consultation with the supplier. Due to continual product research and development, the information contained herein is subject to changes without notification.