

# KAWASAKI WHEELED LOADERS 90 ZIV-2

## CUMMINS M11-C

**ENGINE** Cummins M11C

USE		CLIMATE
Normal		Moderate
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	
<b>Dieselfleet CD+ 15W-40</b>	<b>Multifleet SHPD 15W-40</b>	
<i>Change every 250 hours</i>		

**DIFFERENTIAL HUB REDUCTIONS**

USE		CLIMATE
Normal		Moderate
PRODUCT RECOMMENDATION 1		
<b>Gear Oil Alcat 50</b>		
<i>Change every 2000 hours</i>		

**TRANSMISSION**

USE		CLIMATE
Normal		Moderate
PRODUCT RECOMMENDATION 1		
<b>Multifleet SCD 10W</b>		
<i>Change every 1000 hours</i>		

**HYDRAULIC SYSTEM**

USE		CLIMATE
Normal		Tropical
PRODUCT RECOMMENDATION 1		
<b>Perlus AF 100</b>		
<i>Change every 2000 hours</i>		

USE		CLIMATE
Normal		Mediterranean
PRODUCT RECOMMENDATION 1		
<b>Perlus H 46</b>		
<i>Change every 2000 hours</i>		

USE		CLIMATE
Normal		Arctic
PRODUCT RECOMMENDATION 1		
<b>Perlus H 32</b>		
<i>Change every 2000 hours</i>		

# KAWASAKI WHEELED LOADERS 90 ZIV-2

## CUMMINS M11-C



### HYDRAULIC BRAKE SYSTEM

We are unable to give a standard recommendation for this component. Please contact our service department.

### GREASE POINTS/NIPPLES

USE

Normal

CLIMATE

Moderate

PRODUCT RECOMMENDATION 1

**MoS2 Grease EP 2**

*The data mentioned in this product information sheet is meant to enable the reader to orientate himself about the properties and possible applications of our products. Although this overview is composed with all possible care on the stated date, the compiler does not accept any liability for damages caused by incompleteness and/or inaccuracies in this information, especially when these are caused by obvious typing errors. The terms of delivery of the supplier apply to all product supplies. The reader is advised, especially for critical applications, to make the final product choice in consultation with the supplier. Due to continual product research and development, the information contained herein is subject to changes without notification.*