KIPOR EXCAVATORS KDG KDG35 KIPOR KD388R



| ENGINE Kipor KD338R Capacity: 6,9 liter | | |
|--|--------------------------|--------------------------|
| USE | | CLIMATE |
| Normal | | Moderate |
| PRODUCT RECOMMENDATION 1 | PRODUCT RECOMMENDATION 2 | PRODUCT RECOMMENDATION 3 |
| Kroontrak MTH 10W-30 | Synfleet SHPD 10W-40 | Dieselfleet CD+ 15W-40 |
| Change every 250 hours/ 6 months | | |
| USE | | CLIMATE |
| Initial service | | Moderate |
| PRODUCT RECOMMENDATION 1 | PRODUCT RECOMMENDATION 2 | PRODUCT RECOMMENDATION 3 |
| Kroontrak MTH 10W-30 | Synfleet SHPD 10W-40 | Dieselfleet CD+ 15W-40 |
| | | |

Change every 50 hours

| HYDRAULIC SYSTEM Capacity: 55 liter (Total system volume) | | | |
|--|---|-----------------------|--|
| USE | c | LIMATE | |
| Normal | M | <i>l</i> editerranean | |
| PRODUCT RECOMMENDATION 1 | | | |
| Perlus H 68 | | | |
| Change every 1000 hours | | | |
| USE | c | LIMATE | |
| Normal | N | <i>N</i> oderate | |

| Normal | Moderate |
|--------------------------|----------|
| PRODUCT RECOMMENDATION 1 | |
| Perlus H 46 | |
| Character 1000 hours | |

Change every 1000 hours

| GREASE POINTS/NIPPLES | | | |
|--------------------------|--------------------------|--------------------------|--|
| USE | | CLIMATE | |
| Normal | | Moderate | |
| PRODUCT RECOMMENDATION 1 | PRODUCT RECOMMENDATION 2 | PRODUCT RECOMMENDATION 3 | |
| Q7 MP Calcep Grease WR 2 | Caliplex HD Grease EP 2 | Q5 MP Calcep Grease EP 2 | |

| COOLING SYSTEM | | | | |
|--------------------------|----------|--|--|--|
| USE | CLIMATE | | | |
| Normal | Moderate | | | |
| PRODUCT RECOMMENDATION 1 | | | | |
| Coolant -38 Organic NF | | | | |
| Change every 24 months | | | | |

Change every 24 months

KIPOR EXCAVATORS KDG KDG35 KIPOR KD388R



| TRAVEL REDUCTION UNIT Capacity: 1 liter | | |
|--|------------------------------|----------|
| USE | | CLIMATE |
| Normal | | Moderate |
| PRODUCT RECOMMENDATION 1 | PRODUCT RECOMMENDATION 2 | |
| Gearlube GL-5 85W-140 | Unigear LS GL-3/GL-5 85W-140 | |
| Change every 500 hours | | |
| USE | | CLIMATE |
| Initial service | | Moderate |
| PRODUCT RECOMMENDATION 1 | PRODUCT RECOMMENDATION 2 | |
| Gearlube GL-5 85W-140 | Unigear LS GL-3/GL-5 85W-140 | |
| Change every 100 hours | | |

The data mentioned in this product information sheet is meant to enable the reader to orientate himself about the properties and possible applications of our products. Although this overview is composed with all possible care on the stated date, the compiler does not accept any liability for damages caused by incompleteness and/or inaccuracies in this information, especially when these are caused by obvious typing errors. The terms of delivery of the supplier apply to all product supplies. The reader is advised, especially for critical applications, to make the final product choice in consultation with the supplier. Due to continual product research and development, the information contained herein is subject to changes without notification.