

KOBELCO TRACKED EXCAVATORS

SK17MSR YANMAR 3TNE74 (2001-2003)



ENGINE Yanmar 3TNE74
Capacity: 3,5 liter

USE	CLIMATE
Normal	Tropical

PRODUCT RECOMMENDATION 1

Multifleet SCD 40

Change every 500 hours

USE	CLIMATE
Normal	Mediterranean

PRODUCT RECOMMENDATION 1

Multifleet SCD 30

Change every 500 hours

USE	CLIMATE
Normal	Moderate

PRODUCT RECOMMENDATION 1

Kroontrak MTH 10W-30

PRODUCT RECOMMENDATION 2

Synfleet SHPD 10W-40

PRODUCT RECOMMENDATION 3

Multifleet SHPD 10W-40

Change every 500 hours

USE	CLIMATE
Normal	Cold

PRODUCT RECOMMENDATION 1

Multifleet SCD 10W

Change every 500 hours

HYDRAULIC SYSTEM

Capacity: 14,5 liter (Tank), Capacity: 22 liter (Total)

USE	CLIMATE
Normal	Mediterranean

PRODUCT RECOMMENDATION 1

Perlus H 46

PRODUCT RECOMMENDATION 2

Perlus H 68

Change every 2000 hours

USE	CLIMATE
Normal	Moderate

PRODUCT RECOMMENDATION 1

Perlus H 32

Change every 2000 hours

KOBELCO TRACKED EXCAVATORS

SK17MSR YANMAR 3TNE74 (2001-2003)



GREASE POINTS/NIPPLES

USE		CLIMATE
Normal		Moderate
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	PRODUCT RECOMMENDATION 3
Labora Grease	Q5 MP Calcep Grease EP 2	MP Lithep Grease EP 2

GREASE POINTS/NIPPLES IDLERS

Capacity: 0,03 liter

USE		CLIMATE
Normal		Moderate
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	
Gearlube GL-4 80W-90	Unigear HS GL-3/GL-5 80W-90	

Change every 2000 hours

GREASE POINTS/NIPPLES LOWER ROLLERS

Capacity: 0,06 liter

USE		CLIMATE
Normal		Moderate
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	
Gearlube GL-4 80W-90	Unigear HS GL-3/GL-5 80W-90	

Change every 2000 hours

GREASE POINTS/NIPPLES SWING INTERNAL GEAR

Capacity: 70 grams

USE		CLIMATE
Normal		Moderate
PRODUCT RECOMMENDATION 1		
MoS2 Grease EP 2		

COOLING SYSTEM

Capacity: 1,8 liter (Radiator), Capacity: 2,7 liter (Total)

USE		CLIMATE
Normal		Moderate
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	
Coolant -38 Organic NF	Coolant -26	

KOBELCO TRACKED EXCAVATORS

SK17MSR YANMAR 3TNE74 (2001-2003)



SWING REDUCTION UNIT

USE		CLIMATE
Normal		Mediterranean
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	
Perlus H 46	Perlus H 68	

Change every 2000 hours

USE		CLIMATE
Normal		Moderate
PRODUCT RECOMMENDATION 1		
Perlus H 32		

Change every 2000 hours

TRAVEL REDUCTION UNIT

Capacity: 0,33 liter

USE		CLIMATE
Normal		Moderate
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	PRODUCT RECOMMENDATION 3
Kroontrak MTH 10W-30	Synfleet SHPD 10W-40	Multifleet SHPD 10W-40

Change every 2000 hours

The data mentioned in this product information sheet is meant to enable the reader to orientate himself about the properties and possible applications of our products. Although this overview is composed with all possible care on the stated date, the compiler does not accept any liability for damages caused by incompleteness and/or inaccuracies in this information, especially when these are caused by obvious typing errors. The terms of delivery of the supplier apply to all product supplies. The reader is advised, especially for critical applications, to make the final product choice in consultation with the supplier. Due to continual product research and development, the information contained herein is subject to changes without notification.