KOMATSU BULLDOZERS D D37E-5 KOMATSU S4D102E



ENGINE Komatsu S4D102E-1 Capacity: 12 liter			
USE		CLIMATE	
Normal		Moderate	
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2		
Dieselfleet CD+ 15W-40	Multifleet SHPD 15W-40		
Change every 250 hours/ 6 months	,	<u>'</u>	

BEVEL GEAR BOX

USE

Normal

PRODUCT RECOMMENDATION 1

Gear Oil Alcat 30

Change every 1000 hours

USE

Normal

PRODUCT RECOMMENDATION 1

Gear Oil Alcat 10W

Change every 1000 hours

FINAL DRIVES	
USE	CLIMATE
Normal	Mediterranean
PRODUCT RECOMMENDATION 1	
Gear Oil Alcat 30	
Change every 1000 hours	
USE	CLIMATE
Normal	Cold
PRODUCT RECOMMENDATION 1	
Gear Oil Alcat 10W	
Change every 1000 hours	

KOMATSU BULLDOZERS D D37E-5 KOMATSU S4D102E



TRANSFERBOX	
USE	CLIMATE
Normal	Mediterranean
PRODUCT RECOMMENDATION 1	
Gear Oil Alcat 30	
Change every 1000 hours	
USE	CLIMATE
Normal	Cold
PRODUCT RECOMMENDATION 1	
Gear Oil Alcat 10W	
Change every 1000 hours	
TRANSMISSION	
USE	CLIMATE
Normal	Mediterranean
PRODUCT RECOMMENDATION 1	
Gear Oil Alcat 30	
Change every 1000 hours	
USE	CLIMATE
Normal	Cold
PRODUCT RECOMMENDATION 1	
Gear Oil Alcat 10W	
Change every 1000 hours	
HYDRAULIC SYSTEM	
USE	CLIMATE

HYDRAULIC SYSTEM		
USE		CLIMATE
Normal		Moderate
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	PRODUCT RECOMMENDATION 3
Kroontrak MTH 10W-30	Synfleet SHPD 10W-40	Dieselfleet CD+ 15W-40
Change every 2000 hours		

CARRIER ROLLERS	
USE	CLIMATE
Normal	Moderate
PRODUCT RECOMMENDATION 1	
Gear Oil Alcat 30	
Change every 1000 hours	·

KOMATSU BULLDOZERS D D37E-5 KOMATSU S4D102E



CLIMATE
Mediterranean
CLIMATE
Cold
CLIMATE

Moderate

TRACK ROLLERS	
USE	CLIMATE
Normal	Moderate
PRODUCT RECOMMENDATION 1	
Gear Oil Alcat 30	
Change every 1000 hours	

The data mentioned in this product information sheet is meant to enable the reader to orientate himself about the properties and possible applications of our products. Although this overview is composed with all possible care on the stated date, the compiler does not accept any liability for damages caused by incompleteness and/or inaccuracies in this information, especially when these are caused by obvious typing errors. The terms of delivery of the supplier apply to all product supplies. The reader is advised, especially for critical applications, to make the final product choice in consultation with the supplier. Due to continual product research and development, the information contained herein is subject to changes without notification.

Normal

PRODUCT RECOMMENDATION 1

Gear Oil Alcat 30

Change every 1000 hours