KOMATSU BULLDOZERS D D40A-1 KOMATSU S4D105



USE		CLIMATE
Normal		Moderate
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	
Dieselfleet CD+ 15W-40	Multifleet SHPD 15W-40	
Change every 250 hours/ 6 months	·	·
BEVEL GEAR BOX		
USE		CLIMATE
Normal		Mediterranean
PRODUCT RECOMMENDATION 1		
Gear Oil Alcat 30		
Change every 1000 hours		
USE		CLIMATE
Normal		Cold
PRODUCT RECOMMENDATION 1		
Gear Oil Alcat 10W		
Change every 1000 hours		

FINAL DRIVES	
USE	CLIMATE
Normal	Mediterranean
PRODUCT RECOMMENDATION 1	
Gear Oil Alcat 30	
Change every 1000 hours	
USE	CLIMATE
Normal	Cold
PRODUCT RECOMMENDATION 1	
Gear Oil Alcat 10W	
Change every 1000 hours	

KOMATSU BULLDOZERS D D40A-1 KOMATSU S4D105



TRANSMISSION 4/3	
use Normal	CLIMATE Mediterranean
	ivieulterraneari
PRODUCT RECOMMENDATION 1 Gear Oil Alcat 30	
Change every 1000 hours	O. H.L.Te
use Normal	CLIMATE Cold
PRODUCT RECOMMENDATION 1	
Gear Oil Alcat 10W	
Change every 1000 hours	
HYDRAULIC SYSTEM	
USE	CLIMATE
Normal	Moderate
PRODUCT RECOMMENDATION 1	
Multifleet SCD 10W	
Change every 2000 hours	
CARRIER ROLLERS	
USE	CLIMATE
Normal	Moderate
PRODUCT RECOMMENDATION 1	
Gear Oil Alcat 30	
Change every 1000 hours	
MAIN CLUTCH CASE	
USE	CLIMATE
Normal	Moderate Moderate
PRODUCT RECOMMENDATION 1 Multifleet SCD 10W	
Change every 1000 hours	

KOMATSU BULLDOZERS D D40A-1 KOMATSU S4D105



STEERING CLUTCH CASE				
	CLIMATE			
	Mediterranean			
	CLIMATE			
	Cold			
	CLIMATE			

Moderate

TRACK ROLLERS	
USE	CLIMATE
Normal	Moderate
PRODUCT RECOMMENDATION 1	
Gear Oil Alcat 30	
Change every 1000 hours	

The data mentioned in this product information sheet is meant to enable the reader to orientate himself about the properties and possible applications of our products. Although this overview is composed with all possible care on the stated date, the compiler does not accept any liability for damages caused by incompleteness and/or inaccuracies in this information, especially when these are caused by obvious typing errors. The terms of delivery of the supplier apply to all product supplies. The reader is advised, especially for critical applications, to make the final product choice in consultation with the supplier. Due to continual product research and development, the information contained herein is subject to changes without notification.

Normal

PRODUCT RECOMMENDATION 1

Gear Oil Alcat 30

Change every 1000 hours