

# KOMATSU FORKLIFT TRUCKS, DIESEL - BX50 SERIES -16/17 FD25-16

**ENGINE**

Capacity: 7,5 liter

USE		CLIMATE
Initial service		Moderate
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	PRODUCT RECOMMENDATION 3
<b>Kroontrak MTH 10W-30</b>	<b>Synfleet SHPD 10W-40</b>	<b>Multifleet SHPD 10W-40</b>

*Change every 200 hours***DIFFERENTIAL**

USE		CLIMATE
Initial service		Moderate
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	
<b>Gearlube GL-4 80W-90</b>	<b>Unigear HS GL-3/GL-5 80W-90</b>	

*Change every 200 hours***TORQFLOW TRANSMISSION** Torqflow

Capacity: 9,5 liter

USE		CLIMATE
Initial service		Moderate
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	PRODUCT RECOMMENDATION 3
<b>Kroontrak MTH 10W-30</b>	<b>Synfleet SHPD 10W-40</b>	<b>Multifleet SHPD 10W-40</b>

*Change every 200 hours***HYDRAULIC SYSTEM**

Capacity: 34 liter (Tank)

USE		CLIMATE
Initial service		Moderate
PRODUCT RECOMMENDATION 1		
<b>Multifleet SCD 10W</b>		

*Change every 200 hours***HYDRAULIC BRAKE SYSTEM**

USE		CLIMATE
Normal		Moderate
PRODUCT RECOMMENDATION 1		
<b>Drauliquid DOT 3</b>		

# KOMATSU FORKLIFT TRUCKS, DIESEL - BX50 SERIES -16/17 FD25-16



## HYDRAULIC CLUTCH SYSTEM

USE		CLIMATE
Normal		Moderate
PRODUCT RECOMMENDATION 1		
<b>Drauliquid DOT 3</b>		

## GREASE POINTS/NIPPLES

USE		CLIMATE
Normal		Moderate
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	PRODUCT RECOMMENDATION 3
<b>Labora Grease</b>	<b>Q5 MP Calcep Grease EP 2</b>	<b>MP Lithep Grease EP 2</b>

## COOLING SYSTEM

Capacity: 9,2 liter

USE		CLIMATE
Normal		Moderate
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	
<b>Coolant SP 15+</b>	<b>Coolant SP 12</b>	

The data mentioned in this product information sheet is meant to enable the reader to orientate himself about the properties and possible applications of our products. Although this overview is composed with all possible care on the stated date, the compiler does not accept any liability for damages caused by incompleteness and/or inaccuracies in this information, especially when these are caused by obvious typing errors. The terms of delivery of the supplier apply to all product supplies. The reader is advised, especially for critical applications, to make the final product choice in consultation with the supplier. Due to continual product research and development, the information contained herein is subject to changes without notification.