KOMATSU FORKLIFT TRUCKS, DIESEL - BX50 SERIES -16/17 FD30H-16



ENGINE Capacity: 7,5 liter		
use Initial service		CLIMATE
		Moderate
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	PRODUCT RECOMMENDATION 3
Kroontrak MTH 10W-30	Synfleet SHPD 10W-40	Multifleet SHPD 10W-40
0/ 000/		

Change every 200 hours

DIFFERENTIAL		
USE		CLIMATE
Initial service		Moderate
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	
Gearlube GL-4 80W-90	Unigear HS GL-3/GL-5 80W-90	
Change every 200 hours	'	

TORQFLOW TRANSMISSION Toro Capacity: 9,5 liter	qflow	
use Initial service		CLIMATE
		Moderate
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	PRODUCT RECOMMENDATION 3
Kroontrak MTH 10W-30	Synfleet SHPD 10W-40	Multifleet SHPD 10W-40
Change every 200 hours		<u> </u>

HYDRAULIC SYSTEM Capacity: 34 liter (Tank)	
USE	CLIMATE
Initial service	Moderate
PRODUCT RECOMMENDATION 1	
Multifleet SCD 10W	
Change every 200 hours	·

HYDRAULIC BRAKE SYSTEM	
USE	CLIMATE
Normal	Moderate
PRODUCT RECOMMENDATION 1	
Drauliquid DOT 3	

KOMATSU FORKLIFT TRUCKS, DIESEL - BX50 SERIES -16/17 FD30H-16



HYDRAULIC CLUTCH SYSTEM		
USE	CLIMATE	
Normal	Modera	te
PRODUCT RECOMMENDATION 1		
Drauliquid DOT 3		

Labora Grease	Q5 MP Calcep Grease EP 2	MP Lithep Grease EP 2	
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	PRODUCT RECOMMENDATION 3	
Normal		Moderate	
USE		CLIMATE	
GREASE POINTS/NIPPLES			

COOLING SYSTEM Capacity: 9,2 liter			
use Normal		сымате Moderate	
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2		
Coolant SP 15+	Coolant SP 12		

The data mentioned in this product information sheet is meant to enable the reader to orientate himself about the properties and possible applications of our products. Although this overview is composed with all possible care on the stated date, the compiler does not accept any liability for damages caused by incompleteness and/or inaccuracies in this information, especially when these are caused by obvious typing errors. The terms of delivery of the supplier apply to all product supplies. The reader is advised, especially for critical applications, to make the final product choice in consultation with the supplier. Due to continual product research and development, the information contained herein is subject to changes without notification.