

# KOMATSU FORKLIFT TRUCKS, DIESEL - BX50 SERIES -16/17 FD35A-17 KOMATSU 4D98E (M231-300001 ->)



**ENGINE** Komatsu 4D98E  
Capacity: 7,5 liter

USE	CLIMATE
Normal	Moderate

PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	PRODUCT RECOMMENDATION 3
<b>Kroontrak MTH 10W-30</b>	<b>Synfleet SHPD 10W-40</b>	<b>Multifleet SHPD 10W-40</b>

*Check every 8 hours, change every 1 months/ 200 hours*

**DIFFERENTIAL**  
Capacity: 6 liter

USE	CLIMATE
Normal	Moderate

PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	
<b>Gearlube GL-4 80W-90</b>	<b>Unigear HS GL-3/GL-5 80W-90</b>	

*Check every 1 months/ 200 hours, change every 6 months/ 1200 hours*

**TORQFLOW TRANSMISSION** Torqflow  
Capacity: 9,6 liter

USE	CLIMATE
Normal	Moderate

PRODUCT RECOMMENDATION 1		
<b>Multifleet SCD 10W</b>		

*Check every 1 months/ 200 hours, change every 6 months/ 1200 hours*

**HYDRAULIC SYSTEM**  
Capacity: 55 liter (Hydraulic tank)

USE	CLIMATE
Normal	Moderate

PRODUCT RECOMMENDATION 1		
<b>Multifleet SCD 10W</b>		

*Check every 8 hours, change every 6 months/ 1200 hours*

**HYDRAULIC BRAKE SYSTEM**  
Capacity: 0,15 liter

USE	CLIMATE
Normal	Moderate

PRODUCT RECOMMENDATION 1		
<b>Drauliquid DOT 3</b>		

*Check every 8 hours, change every 6 months/ 1200 hours*

# KOMATSU FORKLIFT TRUCKS, DIESEL - BX50 SERIES -16/17 FD35A-17 KOMATSU 4D98E (M231-300001 ->)



## GREASE POINTS/NIPPLES

USE		CLIMATE
Normal		Moderate
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	PRODUCT RECOMMENDATION 3
<b>Labora Grease</b>	<b>Q5 MP Calcep Grease EP 2</b>	<b>MP Lithep Grease EP 2</b>

## COOLING SYSTEM

Capacity: 9,2 liter

USE		CLIMATE
Normal		Moderate
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	
<b>Coolant SP 15+</b>	<b>Coolant SP 12</b>	

*Check every 8 hours, change every 12 months/ 2400 hours*

*The data mentioned in this product information sheet is meant to enable the reader to orientate himself about the properties and possible applications of our products. Although this overview is composed with all possible care on the stated date, the compiler does not accept any liability for damages caused by incompleteness and/or inaccuracies in this information, especially when these are caused by obvious typing errors. The terms of delivery of the supplier apply to all product supplies. The reader is advised, especially for critical applications, to make the final product choice in consultation with the supplier. Due to continual product research and development, the information contained herein is subject to changes without notification.*