PRODUCT RECOMMENDATION

# KOMATSU FORKLIFT TRUCKS, DIESEL - CX50 SERIES -10 FD50AYT-10 KOMATSU S4D95LE-3

**ENGINE** Komatsu S4D95LE-3
Capacity: 11 liter

| USE | CLIMATE |
|---|---|
| Normal | Moderate |

| PRODUCT RECOMMENDATION 1 | PRODUCT RECOMMENDATION 2 | |
|---|---|---|
| **Synfleet SHPD 10W-40** | **Multifleet SHPD 10W-40** | |

*Check every 8 hours, change every 1 months/ 200 hours*

| USE | CLIMATE |
|---|---|
| Initial service | Moderate |

| PRODUCT RECOMMENDATION 1 | PRODUCT RECOMMENDATION 2 | |
|---|---|---|
| **Synfleet SHPD 10W-40** | **Multifleet SHPD 10W-40** | |

*Change every 1 months/ 200 hours*

**DIFFERENTIAL FRONT**
Capacity: 10 liter

| USE | CLIMATE |
|---|---|
| Normal | Moderate |

| PRODUCT RECOMMENDATION 1 | PRODUCT RECOMMENDATION 2 | |
|---|---|---|
| **SP Gear 5015** | **SP Gear 1071** | |

*Check every 3 months/ 600 hours, change every 6 months/ 1200 hours*

| USE | CLIMATE |
|---|---|
| Initial service | Moderate |

| PRODUCT RECOMMENDATION 1 | PRODUCT RECOMMENDATION 2 | |
|---|---|---|
| **SP Gear 5015** | **SP Gear 1071** | |

*Change every 1 months/ 200 hours*

**TRANSMISSION POWERSHIFT** Torqflow
Capacity: 12 liter

| USE | CLIMATE |
|---|---|
| Normal | Moderate |

| PRODUCT RECOMMENDATION 1 | | |
|---|---|---|
| **Multifleet SCD 10W** | | |

*Check every 1 months/ 200 hours, change every 6 months/ 1200 hours*

| USE | CLIMATE |
|---|---|
| Initial service | Moderate |

| PRODUCT RECOMMENDATION 1 | | |
|---|---|---|
| **Multifleet SCD 10W** | | |

*Change every 1 months/ 200 hours*

KROON-OIL B.V.
Postbus 149
7600 AC Almelo

Dollegoorweg 15
7602 EC Almelo

Telefoon 0546-818165
Verkoop 0546-816184

Telefax 0546-817367

PRODUCT RECOMMENDATION

# KOMATSU FORKLIFT TRUCKS, DIESEL - CX50 SERIES -10 FD50AYT-10 KOMATSU S4D95LE-3

## HYDRAULIC SYSTEM
Capacity: 74 liter (Hydraulic tank)

| USE | | CLIMATE |
|---|---|---|
| Normal | | Moderate |
| PRODUCT RECOMMENDATION 1 | | |
| **Multifleet SCD 10W** | | |

*Check every 8 hours, change every 6 months/ 1200 hours*

| USE | | CLIMATE |
|---|---|---|
| Initial service | | Moderate |
| PRODUCT RECOMMENDATION 1 | | |
| **Multifleet SCD 10W** | | |

*Change every 1 months/ 200 hours*

## GREASE POINTS/NIPPLES

| USE | | CLIMATE |
|---|---|---|
| Normal | | Moderate |
| PRODUCT RECOMMENDATION 1 | PRODUCT RECOMMENDATION 2 | PRODUCT RECOMMENDATION 3 |
| **Labora Grease** | **Q5 MP Calcep Grease EP 2** | **MP Lithep Grease EP 2** |

## COOLING SYSTEM
Capacity: 9 liter

| USE | | CLIMATE |
|---|---|---|
| Normal | | Moderate |
| PRODUCT RECOMMENDATION 1 | PRODUCT RECOMMENDATION 2 | |
| **Coolant SP 15+** | **Coolant SP 12** | |

*Check every 8 hours, change every 24 months/ 2000 hours*

*The data mentioned in this product information sheet is meant to enable the reader to orientate himself about the properties and possible applications of our products. Although this overview is composed with all possible care on the stated date, the compiler does not accept any liability for damages caused by incompleteness and/or inaccuracies in this information, especially when these are caused by obvious typing errors. The terms of delivery of the supplier apply to all product supplies. The reader is advised, especially for critical applications, to make the final product choice in consultation with the supplier. Due to continual product research and development, the information contained herein is subject to changes without notification.*

KROON-OIL B.V.
Postbus 149
7600 AC Almelo

Dollegoorweg 15
7602 EC Almelo

Telefoon 0546-818165
Verkoop 0546-816184

Telefax 0546-817367