

PRODUCT RECOMMENDATION

# KOMATSU FORKLIFT TRUCKS, DIESEL - DX20 SERIES FD70-10 KOMATSU SAA4D95LE-5-A (55001 ->)



**ENGINE** Komatsu SAA4D95LE-5  
Capacity: 11 liter

USE	CLIMATE
Normal	Mediterranean

PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	PRODUCT RECOMMENDATION 3
<b>Agridiesel CRD+ 15W-40</b>	<b>Dieselfleet CD+ 15W-40</b>	<b>Multifleet SHPD 15W-40</b>

*Check every 8 hours, change every 3 months/ 500 hours*

USE	CLIMATE
Normal	Cold

PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	PRODUCT RECOMMENDATION 3
<b>Kroontrak MTH 10W-30</b>	<b>Synfleet SHPD 10W-40</b>	<b>Dieselfleet LSP Ultra 10W-30</b>

*Check every 8 hours, change every 3 months/ 500 hours*

USE	CLIMATE
Initial service	Mediterranean

PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	PRODUCT RECOMMENDATION 3
<b>Agridiesel CRD+ 15W-40</b>	<b>Dieselfleet CD+ 15W-40</b>	<b>Multifleet SHPD 15W-40</b>

*Change every 1 months/ 200 hours*

USE	CLIMATE
Initial service	Cold

PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	PRODUCT RECOMMENDATION 3
<b>Kroontrak MTH 10W-30</b>	<b>Synfleet SHPD 10W-40</b>	<b>Dieselfleet LSP Ultra 10W-30</b>

*Change every 1 months/ 200 hours*

**DIFFERENTIAL FRONT**  
Capacity: 13 liter

USE	CLIMATE
Normal	Moderate

PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2
<b>Gearlube GL-5 80W-90</b>	<b>Unigear HS GL-3/GL-5 80W-90</b>

*Check every 3 months/ 600 hours, change every 6 months/ 1200 hours*

USE	CLIMATE
Initial service	Moderate

PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2
<b>Gearlube GL-5 80W-90</b>	<b>Unigear HS GL-3/GL-5 80W-90</b>

*Change every 1 months/ 200 hours*

# KOMATSU FORKLIFT TRUCKS, DIESEL - DX20 SERIES FD70-10 KOMATSU SAA4D95LE-5-A (55001 ->)

**TRANSMISSION POWERSHIFT Torqflow**

Capacity: 24 liter

USE	CLIMATE
Normal	Moderate

PRODUCT RECOMMENDATION 1

**Multifleet SCD 10W***Check every 1 months/ 200 hours, change every 6 months/ 1200 hours*

USE	CLIMATE
Initial service	Moderate

PRODUCT RECOMMENDATION 1

**Multifleet SCD 10W***Change every 1 months/ 200 hours***HYDRAULIC SYSTEM**

Capacity: 100 liter (Hydraulic tank)

USE	CLIMATE
Normal	Moderate

PRODUCT RECOMMENDATION 1

**Multifleet SCD 10W***Check every 8 hours, change every 6 months/ 1200 hours*

USE	CLIMATE
Initial service	Moderate

PRODUCT RECOMMENDATION 1

**Multifleet SCD 10W***Change every 1 months/ 200 hours***GREASE POINTS/NIPPLES**

USE	CLIMATE
Normal	Moderate

PRODUCT RECOMMENDATION 1

**Labora Grease**

PRODUCT RECOMMENDATION 2

**Q5 MP Calcep Grease EP 2**

PRODUCT RECOMMENDATION 3

**MP Lithep Grease EP 2****COOLING SYSTEM**

Capacity: 9,5 liter

USE	CLIMATE
Normal	Moderate

PRODUCT RECOMMENDATION 1

**Coolant SP 15+**

PRODUCT RECOMMENDATION 2

**Coolant SP 12***Check every 8 hours, change every 6 months/ 1200 hours**The data mentioned in this product information sheet is meant to enable the reader to orientate himself about the properties and possible applications of our products.*

PRODUCT RECOMMENDATION

# KOMATSU FORKLIFT TRUCKS, DIESEL - DX20 SERIES FD70-10 KOMATSU SAA4D95LE-5-A (55001 ->)



*Although this overview is composed with all possible care on the stated date, the compiler does not accept any liability for damages caused by incompleteness and/or inaccuracies in this information, especially when these are caused by obvious typing errors. The terms of delivery of the supplier apply to all product supplies. The reader is advised, especially for critical applications, to make the final product choice in consultation with the supplier. Due to continual product research and development, the information contained herein is subject to changes without notification.*