

KOMATSU FORKLIFT TRUCKS, DIESEL - TUSK BX20 SERIES -14/-16 500PDS-16 KOMATSU 4D98ETIER 2 (200001A ->)



ENGINE Komatsu 4D98E
Capacity: 7,5 liter

USE	CLIMATE
Normal	Moderate

PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	
Synfleet SHPD 10W-40	Multifleet SHPD 10W-40	

Check every 8 hours, change every 1 months/ 200 hours

DIFFERENTIAL
Capacity: 6 liter

USE	CLIMATE
Normal	Moderate

PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	
Gearlube GL-5 80W-90	Unigear HS GL-3/GL-5 80W-90	

Check every 1 months/ 200 hours, change every 6 months/ 1200 hours

TORQFLOW TRANSMISSION Torqflow
Capacity: 9,6 liter

USE	CLIMATE
Normal	Moderate

PRODUCT RECOMMENDATION 1		
ATF Dexron II-D		

Check every 1 months/ 200 hours, change every 6 months/ 1200 hours

HYDRAULIC SYSTEM
Capacity: 58 liter (Hydraulic tank)

USE	CLIMATE
Normal	Moderate

PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	
Perlus H 32	Perlus AF 32	

Check every 8 hours, change every 6 months/ 1200 hours

HYDRAULIC BRAKE SYSTEM
Capacity: 0,15 liter

USE	CLIMATE
Normal	Moderate

PRODUCT RECOMMENDATION 1		
Drauliquid DOT 3		

Check every 8 hours, change every 12 months/ 2400 hours

KOMATSU FORKLIFT TRUCKS, DIESEL - TUSK BX20 SERIES -14/-16 500PDS-16 KOMATSU 4D98ETIER 2 (200001A ->)



GREASE POINTS/NIPPLES

USE

Normal

CLIMATE

Moderate

PRODUCT RECOMMENDATION 1

Labora Grease

PRODUCT RECOMMENDATION 2

Q5 MP Calcep Grease EP 2

PRODUCT RECOMMENDATION 3

MP Lithep Grease EP 2

COOLING SYSTEM

Capacity: 9,2 liter

USE

Normal

CLIMATE

Moderate

PRODUCT RECOMMENDATION 1

Coolant SP 15+

PRODUCT RECOMMENDATION 2

Coolant SP 12

Check every 8 hours, change every 12 months/ 2400 hours

The data mentioned in this product information sheet is meant to enable the reader to orientate himself about the properties and possible applications of our products. Although this overview is composed with all possible care on the stated date, the compiler does not accept any liability for damages caused by incompleteness and/or inaccuracies in this information, especially when these are caused by obvious typing errors. The terms of delivery of the supplier apply to all product supplies. The reader is advised, especially for critical applications, to make the final product choice in consultation with the supplier. Due to continual product research and development, the information contained herein is subject to changes without notification.