

PRODUCT RECOMMENDATION

KOMATSU FORKLIFT TRUCKS, DIESEL - TUSK CX20 SERIES 800/900/1000/1100 1100PD2-8 KOMATSU S6D102E TIER 2



ENGINE Komatsu S6D102E-1
Capacity: 15,1 liter

USE

Normal, low sulphur fuel

CLIMATE

Mediterranean

PRODUCT RECOMMENDATION 1

Multifleet SCD 30

Check every 8 hours, change every 1 months/ 200 hours

USE

Normal, low sulphur fuel

CLIMATE

Moderate

PRODUCT RECOMMENDATION 1

Multifleet SCD 10W

Check every 8 hours, change every 1 months/ 200 hours

USE

Initial service

CLIMATE

Mediterranean

PRODUCT RECOMMENDATION 1

Multifleet SCD 30

Change every 1 months/ 200 hours

USE

Initial service

CLIMATE

Moderate

PRODUCT RECOMMENDATION 1

Multifleet SCD 10W

Change every 1 months/ 200 hours

PRODUCT RECOMMENDATION

KOMATSU FORKLIFT TRUCKS, DIESEL - TUSK CX20 SERIES 800/900/1000/1100 1100PD2-8 KOMATSU S6D102E TIER 2



DIFFERENTIAL

Capacity: 13 liter

USE	CLIMATE
Normal	Moderate

PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	
Gearlube GL-5 80W-90	Unigear HS GL-3/GL-5 80W-90	

Check every 3 months/ 600 hours, change every 6 months/ 1200 hours

USE	CLIMATE
Normal	Arctic

PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	
SP Gear 5015	SP Gear 1071	

Check every 3 months/ 600 hours, change every 6 months/ 1200 hours

USE	CLIMATE
Initial service	Moderate

PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	
Gearlube GL-5 80W-90	Unigear HS GL-3/GL-5 80W-90	

Change every 1 months/ 200 hours

USE	CLIMATE
Initial service	Arctic

PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	
SP Gear 5015	SP Gear 1071	

Change every 1 months/ 200 hours

TRANSMISSION POWERSHIFT Torqflow

Capacity: 16 liter

USE	CLIMATE
Normal	Moderate

PRODUCT RECOMMENDATION 1		
ATF Dexron II-D		

Check every 200 hours, change every 6 months/ 1200 hours

USE	CLIMATE
Initial service	Moderate

PRODUCT RECOMMENDATION 1		
ATF Dexron II-D		

Change every 1 months/ 200 hours

KOMATSU FORKLIFT TRUCKS, DIESEL - TUSK CX20 SERIES 800/900/1000/1100 1100PD2-8 KOMATSU S6D102E TIER 2

**HYDRAULIC SYSTEM**

Capacity: 55 liter

USE		CLIMATE
Normal		Moderate
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	
Perlus H 32	Perlus AF 32	

Check every 8 hours, change every 6 months/ 1200 hours

USE		CLIMATE
Initial service		Moderate
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	
Perlus H 32	Perlus AF 32	

*Change every 1 months/ 200 hours***HYDRAULIC BRAKE SYSTEM**

Capacity: 0,15 liter

USE		CLIMATE
Normal		Moderate
PRODUCT RECOMMENDATION 1		
Drauliquid DOT 3		

*Check every 8 hours, change every 6 months/ 1200 hours***GREASE POINTS/NIPPLES**

USE		CLIMATE
Normal		Moderate
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	PRODUCT RECOMMENDATION 3
Labora Grease	Q5 MP Calcep Grease EP 2	MP Lithep Grease EP 2

COOLING SYSTEM

Capacity: 14 liter

USE		CLIMATE
Normal		Moderate
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	
Coolant -38 Organic NF	Coolant -26	

Check every 8 hours, change every 12 months/ 2400 hours

The data mentioned in this product information sheet is meant to enable the reader to orientate himself about the properties and possible applications of our products. Although this overview is composed with all possible care on the stated date, the compiler does not accept any liability for damages caused by incompleteness and/or inaccuracies in this information, especially when these are caused by obvious typing errors. The terms of delivery of the supplier apply to all product supplies. The reader is advised, especially for critical applications, to make the final product choice in consultation with the supplier. Due to continual product research and development, the information contained herein is subject to changes without notification.