

KOMATSU FORKLIFT TRUCKS, ELECTRIC - BBX50 SERIES -6 FB25SH-6 BBX (90001A - >/ 93001->)

**DIFFERENTIAL + TRANSFERBOX**

Capacity: 8 liter

USE		CLIMATE
Normal		Moderate

PRODUCT RECOMMENDATION 1

SP Gear 5015

PRODUCT RECOMMENDATION 2

SP Gear 1071*Check every 3 months/ 600 hours, change every 6 months/ 1200 hours*

USE		CLIMATE
Initial service		Moderate

PRODUCT RECOMMENDATION 1

SP Gear 5015

PRODUCT RECOMMENDATION 2

SP Gear 1071*Change every 1 months/ 200 hours***HYDRAULIC SYSTEM**

Capacity: 33 liter

USE		CLIMATE
Normal		Moderate

PRODUCT RECOMMENDATION 1

Perlus H 32

PRODUCT RECOMMENDATION 2

Perlus AF 32*Check every 8 hours, change every 6 months/ 1200 hours*

USE		CLIMATE
Initial service		Moderate

PRODUCT RECOMMENDATION 1

Perlus H 32

PRODUCT RECOMMENDATION 2

Perlus AF 32*Change every 1 months/ 200 hours***HYDRAULIC BRAKE SYSTEM**

Capacity: 0,15 liter

USE		CLIMATE
Normal		Moderate

PRODUCT RECOMMENDATION 1

Drauliquid DOT 3*Check every 8 hours, change every 6 months/ 1200 hours*

KOMATSU FORKLIFT TRUCKS, ELECTRIC - BBX50 SERIES -6 FB25SH-6 BBX (90001A - >/ 93001->)



GREASE POINTS/NIPPLES

USE		CLIMATE
Normal		Moderate
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	PRODUCT RECOMMENDATION 3
Labora Grease	Q5 MP Calcep Grease EP 2	MP Lithep Grease EP 2

The data mentioned in this product information sheet is meant to enable the reader to orientate himself about the properties and possible applications of our products. Although this overview is composed with all possible care on the stated date, the compiler does not accept any liability for damages caused by incompleteness and/or inaccuracies in this information, especially when these are caused by obvious typing errors. The terms of delivery of the supplier apply to all product supplies. The reader is advised, especially for critical applications, to make the final product choice in consultation with the supplier. Due to continual product research and development, the information contained herein is subject to changes without notification.