

KOMATSU FORKLIFT TRUCKS, ELECTRIC

FB FB25RW-1R



REDUCTION GEARS

Capacity: 3,8 liter

USE	CLIMATE
Normal	Arctic

PRODUCT RECOMMENDATION 1

ATF-A*Change every 6 months/ 1200 hours*

USE	CLIMATE
Initial service	Arctic

PRODUCT RECOMMENDATION 1

ATF-A*Change every 200 hours*

HYDRAULIC SYSTEM

Capacity: 25 liter

USE	CLIMATE
Normal	Moderate

PRODUCT RECOMMENDATION 1

Perlus H 32*Change every 6 months/ 1200 hours*

USE	CLIMATE
Normal	Arctic

PRODUCT RECOMMENDATION 1

ATF-A*Change every 6 months/ 1200 hours*

USE	CLIMATE
Initial service	Moderate

PRODUCT RECOMMENDATION 1

Perlus H 32*Change every 200 hours*

USE	CLIMATE
Initial service	Arctic

PRODUCT RECOMMENDATION 1

ATF-A*Change every 200 hours*

KOMATSU FORKLIFT TRUCKS, ELECTRIC FB FB25RW-1R



HYDRAULIC BRAKE SYSTEM

USE		CLIMATE
Normal		Moderate
PRODUCT RECOMMENDATION 1		
Drauliquid DOT 3		

Change every 6 months/ 1200 hours

GREASE POINTS/NIPPLES

USE		CLIMATE
Normal		Moderate
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	PRODUCT RECOMMENDATION 3
Labora Grease	Q5 MP Calcep Grease EP 2	MP Lithep Grease EP 2

The data mentioned in this product information sheet is meant to enable the reader to orientate himself about the properties and possible applications of our products. Although this overview is composed with all possible care on the stated date, the compiler does not accept any liability for damages caused by incompleteness and/or inaccuracies in this information, especially when these are caused by obvious typing errors. The terms of delivery of the supplier apply to all product supplies. The reader is advised, especially for critical applications, to make the final product choice in consultation with the supplier. Due to continual product research and development, the information contained herein is subject to changes without notification.