KOMATSU FORKLIFT TRUCKS, ELECTRIC - TUSK ABX/BSX/CBX 300CBSH-7 ABX (85001A ->)



DIFFERENTIAL + TRANSFERBOX Capacity: 10 liter				
USE		CLIMATE		
Normal		Moderate		
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2			
Gearlube GL-5 80W-90	Unigear HS GL-3/GL-5 80W-90			
Check every 3 months/ 600 hours, change every 6 months/ 1200 hours				
USE		CLIMATE		
Initial service		Moderate		
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2			
Gearlube GL-5 80W-90	Unigear HS GL-3/GL-5 80W-90			

HYDRAULIC SYSTEM Capacity: 31 liter	
USE	CLIMATE
Normal	Moderate
PRODUCT RECOMMENDATION 1	
Multifleet SCD 10W	

Check every 8 hours, change every 6 months/ 1200 hours

USE		CLIMATE
Initial service		Moderate
PRODUCT RECOMMENDATION 1		
Multifleet SCD 10W		

Change every 1 months/ 200 hours

Change every 1 months/ 200 hours

HYDRAULIC BRAKE SYSTEM Capacity: 0,15 liter		
USE	CLIMAT	Е
Normal	Mode	rate
PRODUCT RECOMMENDATION 1		
Drauliquid DOT 3		
Check every 8 hours, change every 6 months/ 1200 hours		

KOMATSU FORKLIFT TRUCKS, ELECTRIC - TUSK ABX/BSX/CBX 300CBSH-7 ABX (85001A ->)



GREASE POINTS/NIPPLES			
USE		CLIMATE	
Normal		Moderate	
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	PRODUCT RECOMMENDATION 3	
Labora Grease	Q5 MP Calcep Grease EP 2	MP Lithep Grease EP 2	

The data mentioned in this product information sheet is meant to enable the reader to orientate himself about the properties and possible applications of our products. Although this overview is composed with all possible care on the stated date, the compiler does not accept any liability for damages caused by incompleteness and/or inaccuracies in this information, especially when these are caused by obvious typing errors. The terms of delivery of the supplier apply to all product supplies. The reader is advised, especially for critical applications, to make the final product choice in consultation with the supplier. Due to continual product research and development, the information contained herein is subject to changes without notification.