## KOMATSU FORKLIFT TRUCKS, LPG/PETROL FG FG10H-16



ENGINE		
USE		CLIMATE
Normal		Moderate
PRODUCT RECOMMENDATION 1		
Kroontrak MTH 10W-30		
Change every 200 hours		
DIFFERENTIAL		
USE		CLIMATE
Normal		Moderate
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	
Gearlube GL-5 80W-90	Unigear HS GL-3/GL-5 80W-90	

USE

Normal Cold

PRODUCT RECOMMENDATION 1 PRODUCT RECOMMENDATION 2

SP Gear 5015 SP Gear 1071

Change every 6 months/ 1200 hours

Change every 6 months/ 1200 hours

Initial service

PRODUCT RECOMMENDATION 1

Gearlube GL-5 80W-90

PRODUCT RECOMMENDATION 2

Unigear HS GL-3/GL-5 80W-90

CLIMATE

Change every 200 hours

Initial service Cold

PRODUCT RECOMMENDATION 1 PRODUCT RECOMMENDATION 2

SP Gear 5015 SP Gear 1071

Change every 200 hours

## KOMATSU FORKLIFT TRUCKS, LPG/PETROL FG FG10H-16



TORQFLOW TRANSMISSION Torqflow		
USE		CLIMATE
Normal		Moderate
PRODUCT RECOMMENDATION 1		
Multifleet SCD 10W		
Change every 3 months/ 600 hours		
USE		CLIMATE
Initial service		Moderate
PRODUCT RECOMMENDATION 1		
Multifleet SCD 10W		
Change every 200 hours	-	
HYDRAULIC SYSTEM		

USE	CLIMATE
Normal	Moderate
PRODUCT RECOMMENDATION 1	
Multifleet SCD 10W	
Change every 6 months/ 1200 hours	
USE	CLIMATE
use Initial service	CLIMATE Moderate
Initial service	

HYDRAULIC BRAKE SYSTEM	
USE	CLIMATE
Normal	Moderate
PRODUCT RECOMMENDATION 1	
Drauliquid DOT 3	
Change every 6 months/ 1200 hours	,

GREASE POINTS/NIPPLES			
USE		CLIMATE	
Normal		Moderate	
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	PRODUCT RECOMMENDATION 3	
Labora Grease	Q5 MP Calcep Grease EP 2	MP Lithep Grease EP 2	

PRODUCT RECOMMENDATION

## KOMATSU FORKLIFT TRUCKS, LPG/PETROL FG FG10H-16



The data mentioned in this product information sheet is meant to enable the reader to orientate himself about the properties and possible applications of our products. Although this overview is composed with all possible care on the stated date, the compiler does not accept any liability for damages caused by incompleteness and/or inaccuracies in this information, especially when these are caused by obvious typing errors. The terms of delivery of the supplier apply to all product supplies. The reader is advised, especially for critical applications, to make the final product choice in consultation with the supplier. Due to continual product research and development, the information contained herein is subject to changes without notification.