

# KOMATSU FORKLIFT TRUCKS, LPG/PETROL - AX50 SERIES -20 FG18HC-20 NISSAN K21 (M221-650001 ->)



**ENGINE** Nissan K21  
Capacity: 3,8 liter

USE	CLIMATE
Normal	Moderate

PRODUCT RECOMMENDATION 1

**Synfleet SHPD 10W-40**

PRODUCT RECOMMENDATION 2

**Dieselfleet MSP 10W-30**

*Check every 8 hours, change every 3 months/ 500 hours*

## CLUTCH TRANSMISSION

Capacity: 9,6 liter

USE	CLIMATE
Normal	Moderate

PRODUCT RECOMMENDATION 1

**Gearlube GL-4 80W-90**

PRODUCT RECOMMENDATION 2

**Unigear HS GL-3/GL-5 80W-90**

*Check every 1 months/ 200 hours, change every 6 months/ 1200 hours*

## DIFFERENTIAL

Capacity: 4,5 liter

USE	CLIMATE
Normal	Moderate

PRODUCT RECOMMENDATION 1

**Gearlube GL-4 80W-90**

PRODUCT RECOMMENDATION 2

**Unigear HS GL-3/GL-5 80W-90**

*Check every 1 months/ 200 hours, change every 6 months/ 1200 hours*

## HYDRAULIC SYSTEM

Capacity: 40 liter (Hydraulic tank)

USE	CLIMATE
Normal	Moderate

PRODUCT RECOMMENDATION 1

**Multifleet SCD 10W**

*Check every 8 hours, change every 6 months/ 1200 hours*

## HYDRAULIC BRAKE SYSTEM

Capacity: 0,15 liter

USE	CLIMATE
Normal	Moderate

PRODUCT RECOMMENDATION 1

**Drauliquid DOT 3**

*Check every 8 hours, change every 6 months/ 1200 hours*

# KOMATSU FORKLIFT TRUCKS, LPG/PETROL - AX50 SERIES -20 FG18HC-20 NISSAN K21 (M221-650001 ->)



## GREASE POINTS/NIPPLES

### USE

Normal

### CLIMATE

Moderate

### PRODUCT RECOMMENDATION 1

**Labora Grease**

### PRODUCT RECOMMENDATION 2

**Q5 MP Calcep Grease EP 2**

### PRODUCT RECOMMENDATION 3

**MP Lithep Grease EP 2**

## COOLING SYSTEM

Capacity: 9,1 liter

### USE

Normal

### CLIMATE

Moderate

### PRODUCT RECOMMENDATION 1

**Coolant SP 15+**

### PRODUCT RECOMMENDATION 2

**Coolant SP 12**

*Check every 8 hours, change every 12 months/ 2400 hours*

*The data mentioned in this product information sheet is meant to enable the reader to orientate himself about the properties and possible applications of our products. Although this overview is composed with all possible care on the stated date, the compiler does not accept any liability for damages caused by incompleteness and/or inaccuracies in this information, especially when these are caused by obvious typing errors. The terms of delivery of the supplier apply to all product supplies. The reader is advised, especially for critical applications, to make the final product choice in consultation with the supplier. Due to continual product research and development, the information contained herein is subject to changes without notification.*